

## Brother MFC-L5710DW Laser A4 1200 x 1200 DPI 48 ppm Wi-Fi

Brand: Brother Product code: MFCL5710DWQJ1

**Product name : MFC-L5710DW** 

A4, Electrophotographic Laser Printer, 48 pages/min, 1200×1200 dpi, LAN, WLAN Brother MFC-L5710DW. Print technology: Laser, Printing: Mono printing, Maximum resolution: 1200 x 1200 DPI. Copying: Mono copying, Maximum copy resolution: 1200 x 600 DPI. Scanning: Colour scanning, Optical scanning resolution: 1200 x 1200 DPI. Faxing: Mono faxing. Duplex functions: Copy, Fax, Print, Scan. Maximum ISO A-series paper size: A4. Wi-Fi. Product colour: Black, White



Printing		Paper handling	
Duplex printing mode Print technology * Printing *	Auto Laser Mono printing	JIS B-series sizes (B0B9) Envelopes sizes Paper tray media weight	B5 C5, Com-10, DL, Monarch 60 - 230 g/m²
Duplex printing *	1000 1000 001	Ports & interfaces	
Maximum resolution * Print speed (black, normal quality, A4/US Letter) *	1200 x 1200 DPI 48 ppm	USB port USB connector	✓ USB Type-A / USB Type-B
Time to first page (black, normal)	6.7 s	Network	
Copying		Wi-Fi *	✓
Duplex copying * Duplex copying mode	<b>✓</b> Auto	Ethernet LAN * Cabling technology	10/100/1000Base-T(X)
Copying *  Maximum copy resolution *	Mono copying 1200 x 600 DPI	Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n) WPA2-AES, 64-bit WEP, WPA2-PSK,
Time to first copy (black, normal)  Maximum number of copies	8.7 s 999 copies	Security algorithms	128-bit WEP, WPA2-TKIP, WPA3- SAE, WPA-AES, WPA-PSK, WPA-TKIP
Copier resize  Scanning	25 - 400%		ARP, RARP, BOOTP, DHCP, APIPA (Auto IP), WINS/NetBIOS name resolution, DNS Resolver, mDNS,
Duplex scanning * Duplex scanning mode Scanning * Optical scanning resolution * Scanner type * Input colour depth	Auto Colour scanning 1200 x 1200 DPI ADF scanner 48 bit	Supported network protocols (IPv4)	LLMNR responder, LPR/LPD, Custom Raw Port/Port9100, POP3, SMTP Client, IPP/IPPS, FTP Client and Server, CIFS Client, TELNET Server, SNMPv1/v2c/v3, HTTP/HTTPS server, TFTP client and server, ICMP, Web Services (Print/Scan), SNTP Client, LDAP, IMAP4, Syslog
Output colour depth Input greyscale depth Output greyscale depth Scan drivers	16 bit 16 bit 8 bit TWAIN, WIA	Supported network protocols (IPv6)	NDP, RA, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port9100, IPP/IPPS, POP3, SMTP Client, FTP Client and Server, CIFS Client, TELNET Server, SNMPv1/v2c/v3, HTTP/HTTPS server, TFTP client and server, ICMPv6, SNTP Client, LDAP, Web Services (Print/Scan), IMAP4, Syslog
Fax  Duplex faxing	<b>✓</b>		
Faxing * Modem speed	Mono faxing 33.6 Kbit/s	Performance	
Fax memory Auto-redialing	500 pages	Internal memory * Sound pressure level (printing)	512 MB 54 dB
Features		Design	
Duplex functions * Number of print cartridges * Printing colours * Page description languages	Copy, Fax, Print, Scan  1  Black PDF, BR-Script 3, PCL 6, XPS	Product colour *  Market positioning *  Built-in display *  Display	Black, White Home & office ✓ TFT
Input & output capacity		Display diagonal	8.89 cm (3.5")
Total number of input trays * Total input capacity *	1 250 sheets	Control type Colour display	Touch ✓

Input & output capacity		Power	
Total output capacity * Auto document feeder (ADF) Maximum input capacity  Paper handling	150 sheets  ✓ 1390 sheets	Power consumption (printing) Power consumption (copying) Power consumption (ready) Power consumption (sleep) Power consumption (off) AC input voltage AC input frequency	670 W 680 W 31 W 5.9 W
Maximum ISO A-series paper size *  Paper tray media types *	A4 Bond paper, Envelopes, Labels, Letterhead, Plain paper, Postcard, Recycled paper, Thick paper, Thin paper A4, A5 Executive, Folio, Legal, Letter		0.05 W 220 - 240 V 50/60 Hz
ISO A-series sizes (A0A9) * Non-ISO print media sizes		System requirements Windows operating systems supported	Windows 10, Windows 11
		Operational conditions	
		Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H)	20 - 80% 0 - 40 °C 10 - 32.5 °C 35 - 85%
		Weight & dimensions	
		Width Depth Height Weight	417 mm 461 mm 448 mm 16.4 kg
		Packaging data	
		Package weight	20 kg

