## Brother MFC-L5710DN Laser A4 1200 x 1200 DPI 48 ppm

Brand : Brother

Product code: MFCL5710DNQJ1

Product name : MFC-L5710DN

A4, Electrophotographic Laser Printer, 48 pages/min, 1200×1200 dpi, LAN Brother MFC-L5710DN. Print technology: Laser, Printing: Mono printing, Maximum resolution: 1200 x 1200 DPI. Copying: Mono copying, Maximum copy resolution: 1200 x 600 DPI. Scanning: Colour scanning, Optical scanning resolution: 1200 x 1200 DPI. Faxing: Mono faxing. Duplex functions: Copy, Fax, Print, Scan. Maximum ISO A-series paper size: A4. Product colour: Black, White



Printing		Paper handling	
Duplex printing mode Print technology * Printing *	Auto Laser Mono printing	JIS B-series sizes (B0B9) Envelopes sizes Paper tray media weight	B5 C5, Com-10, DL, Monarch 60 - 230 g/m²
Duplex printing *	✓	Ports & interfaces	
Maximum resolution * Print speed (black, normal quality,	1200 x 1200 DPI	USB port	4
A4/US Letter) *	48 ppm	USB connector	USB Type-A / USB Type-B
Time to first page (black, normal)	6.7 s	Network	
Copying		Wi-Fi *	×
Duplex copying *	<b>√</b>	Ethernet LAN * Cabling technology	✓ 10/100/1000Base-T(X)
Duplex copying mode Copying * Maximum copy resolution *	Auto Mono copying 1200 x 600 DPI	Security algorithms	WPA2-AES, 64-bit WEP, WPA2-PSK, 128-bit WEP, WPA2-TKIP, WPA3- SAE, WPA-AES, WPA-PSK, WPA-TKIP
Time to first copy (black, normal) Maximum number of copies Copier resize	8.7 s 999 copies 25 - 400%		ARP, RARP, BOOTP, DHCP, APIPA (Auto IP), WINS/NetBIOS name resolution, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port9100, POP3, SMTP Client, IPP/IPPS, FTP Client and Server, CIFS Client, TELNET Server, SNMPv1/v2c/v3, HTTP/HTTPS server, TFTP client and server, ICMP, Web Services (Print/Scan), SNTP Client, LDAP, IMAP4, Syslog
Scanning		Supported network protocols (IPv4)	
Duplex scanning * Duplex scanning mode Scanning * Optical scanning resolution *	✓ Auto Colour scanning 1200 x 1200 DPI	Supported network protocols (IPV4)	
Scanner type * Input colour depth Output colour depth Input greyscale depth Output greyscale depth Scan drivers Fax	ADF scanner 48 bit 16 bit 16 bit 8 bit TWAIN, WIA	Supported network protocols (IPv6)	NDP, RA, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port9100, IPP/IPPS, POP3, SMTP Client, FTP Client and Server, CIFS Client, TELNET Server, SNMPv1/v2c/v3, HTTP/HTTPS server, TFTP client and server, ICMPv6, SNTP Client, LDAP, Web Services (Print/Scan), IMAP4, Syslog
Duplex faxing	1	Performance	(11111,0call), 11,11 1, 59510g
Faxing * Modem speed	Mono faxing 33.6 Kbit/s	Internal memory * Sound pressure level (printing)	512 MB 54 dB
Fax memory Auto-redialing	500 pages	Design	
J.	•	Product colour *	Black, White
Features Duplex functions * Number of print cartridges * Printing colours * Page description languages	Copy, Fax, Print, Scan 1 Black PDF, BR-Script 3, PCL 6, XPS	Market positioning * Built-in display * Display Display diagonal Control type	Home & office ✓ TFT 8.89 cm (3.5") Touch
Input & output capacity		Colour display	1
Total number of input trays *	1	Power	
Total input capacity *	250 sheets	Power consumption (printing)	670 W

Input & output capacity		Power	
Total output capacity * Auto document feeder (ADF) Maximum input capacity	150 sheets ✓ 1390 sheets	Power consumption (copying) Power consumption (ready) Power consumption (sleep) Power consumption (off) AC input voltage AC input frequency	680 W 31 W 5.9 W 0.05 W
Paper handling	A4 Bond paper, Envelopes, Labels, Letterhead, Plain paper, Postcard, Recycled paper, Thick paper, Thin paper A4, A5		
Maximum ISO A-series paper size *			220 - 240 V 50/60 Hz
Paper tray media types *		System requirements	
ISO A-series sizes (A0A9) *		Windows operating systems supported	Windows 10, Windows 11
Non-ISO print media sizes	Executive, Folio, Legal, Letter	Operational conditions	
		Operating relative humidity (H-H) Storage temperature (T-T) Operating temperature (T-T) Storage relative humidity (H-H)	20 - 80% 0 - 40 °C 10 - 32.5 °C 35 - 85%
		Weight & dimensions	

Width

Depth

Height

Weight

Packaging data Package weight 417 mm

461 mm

448 mm

16.6 kg

20 kg

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.