

## DELL UltraSharp U2724DE computer monitor 68.6 cm (27") 2560 x 1440 pixels Quad HD LCD Black, Silver

Brand : DELL Product family: UltraSharp Product code: DELL-U2724DE

**Product name:** U2724DE

- 68.6cm (27") Quad HD 2560 x 1440 Edge LED IPS
- 8ms, 16:9, 350cd/m<sup>2</sup>, 2000:1
- USB, HDMI, DisplayPort

68.6cm (27") Quad HD 2560 x 1440 Edge LED IPS, 16:9, 350cd/m², 1.07B, 8ms, 178°/178°, 2000:1

DELL UltraSharp U2724DE computer monitor 68.6 cm (27")  $2560 \times 1440 \text{ pixels}$  Quad HD LCD Black, Silver:

Experience a new level of visual comfort and productivity with this hub monitor certified by TÜV for 5-star eye comfort. Designed with extensive connectivity and the power of Thunderbolt 4. DELL UltraSharp U2724DE. Display diagonal: 68.6 cm (27"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub. VESA mounting, Height adjustment. Product colour: Black, Silver











Display		Ergonomics	
Display diagonal *	68.6 cm (27")	Panel mounting interface	100 x 100 mm
Display resolution *	2560 x 1440 pixels	Cable management	✓
HD type *	Quad HD	Cable lock slot *	✓
Native aspect ratio *	16:9	Cable lock slot type	Kensington
Display technology *	LCD	Height adjustment *	✓
Panel type *	IPS	Height adjustment	15 cm
Backlight type	Edge LED	Pivot	✓
Touchscreen *	×	Pivot angle	-90 - 90°
Display brightness (typical)	350 cd/m <sup>2</sup>	Swivelling	✓
Response time	8 ms	Swivel angle range	-45 - 45°
Anti-glare screen	✓	Tilt adjustment	✓
Screen shape *	Flat	Tilt angle range	-5 - 21°
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1600 x 1200 (UXGA), 1600 x 900, 1920 x 1080 (HD 1080), 2048 x 1080, 2560	On Screen Display (OSD)	✓
		Plug and Play	✓
		Power	
		Energy efficiency class (SDR) *	F
	x 1440	Energy efficiency class (HDR) *	Not available
Supported video modes Contrast ratio (typical) *	480p, 576p, 720p, 1080i, 1080p 2000:1	Energy consumption (SDR) per 1000 hours *	24 kWh
Maximum refresh rate *	120 Hz	Power consumption (typical) *	24.4 W
Viewing angle, horizontal	178°	Power consumption (standby) *	0.5 W
3 3 1	2.0		
Viewing angle, vertical	178°	Power consumption (max)	225 W
Viewing angle, vertical  Display number of colours *	178° 1.07 billion colours	Power consumption (max) Power consumption (off)	225 W 0.3 W
Display number of colours *	178° 1.07 billion colours 5 ms	• • • • •	
Display number of colours * Response time (fast)	1.07 billion colours	Power consumption (off)	0.3 W
Display number of colours *	1.07 billion colours 5 ms	Power consumption (off) AC input voltage	0.3 W 100 - 240 V
Display number of colours * Response time (fast) Pixel pitch	1.07 billion colours 5 ms 0.2331 x 0.2331 mm	Power consumption (off) AC input voltage AC input frequency	0.3 W 100 - 240 V 50/60 Hz
Display number of colours * Response time (fast) Pixel pitch Pixel density	1.07 billion colours 5 ms 0.2331 x 0.2331 mm 108.97 ppi	Power consumption (off) AC input voltage AC input frequency Input current	0.3 W 100 - 240 V 50/60 Hz 2.65 A
Display number of colours * Response time (fast) Pixel pitch Pixel density Viewable size, horizontal	1.07 billion colours 5 ms 0.2331 x 0.2331 mm 108.97 ppi 59.7 cm	Power consumption (off) AC input voltage AC input frequency Input current Power supply type	0.3 W 100 - 240 V 50/60 Hz 2.65 A
Display number of colours * Response time (fast) Pixel pitch Pixel density Viewable size, horizontal Viewable size, vertical	1.07 billion colours 5 ms 0.2331 x 0.2331 mm 108.97 ppi 59.7 cm 33.6 cm	Power consumption (off) AC input voltage AC input frequency Input current Power supply type Operational conditions	0.3 W 100 - 240 V 50/60 Hz 2.65 A Internal

Display		Operational conditions	
High Dynamic Range (HDR) supported Surface hardness Colour depth	X 3H 8 bit	Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	10 - 80% 5 - 90% 0 - 5000 m 5000 - 12192 m
RGB colour space	DCI-P3	Packaging content	
Colour gamut	98%		,
sRGB coverage (typical)	100%	Stand included	✓ AC, DisplayPort, Thunderbolt, USB
Performance		Cables included	Type-A to USB Type-C
NVIDIA G-SYNC *  AMD FreeSync *  Flicker-free technology  Low Blue Light technology	× × ✓	Power adapter included Remote control included Stylus included Quick start guide	× ×
Multimedia		Weight & dimensions	
Built-in speaker(s) * Built-in camera *  Design	×	Width (with stand) Depth (with stand) Height (with stand)	612.2 mm 192.3 mm 535.6 mm
Market positioning *	Business	Weight (with stand)	6.98 kg
Product colour *	Black, Silver	Width (without stand)	612.2 mm
Front bezel colour	Black	Depth (without stand)	50.1 mm
Feet colour	Silver	Height (without stand) Weight (without stand)	352.5 mm 5.23 kg
Ports & interfaces		Bezel width (side)	7.75 mm
Built-in USB hub *	✓	Bezel width (top)	7.75 mm
USB upstream port type	USB Type-C	Bezel width (bottom)	9.1 mm
Number of upstream ports	1	Packaging data	
Number of USB Type-C upstream	1	Package weight	10.2 kg
ports quantity USB Type-A downstream ports		Sustainability	g
quantity	4	Sustainability compliance	1
USB Type-C downstream ports quantity	1	Sustainability certificates Doesn't contain	ENERGY STAR, RoHS, TCO PVC/BFR
USB Type-C DisplayPort Alternate Mode	✓	European Product Registry for Energy Labelling (EPREL) code	1591641
USB Power Delivery	<b>√</b>		
USB Power Delivery up to HDMI *	90 W ✓	Carbon footprint	
HDMI ports quantity	1	Total carbon footprint	649 kg of CO2e
HDMI version	2.1	Total carbon emissions (Standard deviation)	152 kg of CO2e
DisplayPorts quantity	2	Carbon emissions (Manufacturing)	412 kg of CO2e
DisplayPort version	1.4	Carbon emissions (Logistics)	49 kg of CO2e
Thunderbolt 4 ports quantity	2	Carbon emissions (Use)	182 kg of CO2e
Headphone out *	<b>√</b>	Carbon emissions (End-of-Life)	6 kg of CO2e
Microphone in	X	Total carbon emissions (w/o Use phase)	467 kg of CO2e
PC Audio in HDCP	×	PAIA version	1.3.2
HDCP version	1.4	Other features	
AC (power) in	<b>✓</b>	RJ-45 ports quantity	1
Network		ing its points quantity	-
Wi-Fi	×		
Ethernet LAN	✓		
Ergonomics			
VESA mounting *	<b>√</b>		
*LSA injuning	•		



5397184821480

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.