

Lindy 43388 interface hub USB 3.2 Gen 1 (3.1 Gen 1) Type-A 5000 Mbit/s Black, Grey

Brand: Lindy Product code: 43388

Product name: 43388

5m USB 3.0 Hub 4 Ports

Lindy 43388 interface hub USB 3.2 Gen 1 (3.1 Gen 1) Type-A 5000 Mbit/s Black, Grey:

The Lindy 5m USB 3.0 Hub uses built-in active electronics to extend the cable length of up to four USB devices by an additional 5m. It provides 2 USB Type A and 2 USB Type C SuperSpeed ports for connecting up to 4 peripherals such as storage devices, printers or webcams to a USB Type A equipped computer at longer distances, while also ensuring flexible positioning. Capable of data transfer speeds of up to 5Gbps, the hub is also backwards compatible with USB 2.0 and 1.1.

The hub is powered by the USB Bus, while it also features a DC socket for connecting an external 5VDC power supply (not included) when using USB peripherals which have higher power requirements. With 'Plug and Play' installation, no drivers are required, therefore this hub can be installed with minimum difficulty.











Ports & interfaces		Weight & dimensions	
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-A	Height	14 mm
Hub interfaces *	USB 3.2 Gen 1 (3.1 Gen 1) Type-A, USB 3.2 Gen 1 (3.1 Gen 1) Type-C	Weight	281 g
USB 3.2 Gen 1 (3.1 Gen 1) Type-A		Packaging data	
ports quantity	2	Quantity per pack	1 pc(s)
USB 3.2 Gen 1 (3.1 Gen 1) Type-C	2	Package width	236 mm
ports quantity	4	Package depth	255 mm
Ports quantity *	4	Package height	40 mm
DC-in jack	*	Package weight	300 g
Features		Package type	Polybag
Data transfer rate *	5000 Mbit/s	Operational conditions	
Product colour	Black, Grey	Maximum operating temperature	45 °C
Housing material	Aluminium, Plastic	Operating temperature (T-T)	0 - 45 °C
Cable length	5 m	Operating temperature (T-T)	32 - 113 °F
Power		Storage temperature (T-T)	-20 - 70 °C
Input voltage	5 V	Operating relative humidity (H-H)	0 - 40%
Input current	0.9 A	Sustainability	
Weight & dimensions		Sustainability compliance	✓
Width	52.5 mm	Sustainability certificates C	CE, Federal Communications
Depth	52.5 mm		Commission (FCC), REACH, RoHS, UKCA



4002888433884

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.