ASUS Dual -RTX4070S-O12G NVIDIA GeForce RTX 4070 SUPER 12 GB GDDR6X

Brand : ASUS Product family: Dual Product code: 90YV0K82-M0NA00

Product name: DUAL-RTX4070S-O12G

- Powered by NVIDIA DLSS3, ultra-efficient Ada Lovelace arch, and full ray tracing
- 4th Generation Tensor Cores: Up to 4x performance with DLSS 3 vs. brute-force rendering
- 3rd Generation RT Cores: Up to 2x ray tracing performance
- OC edition: Boost Clock 2550 MHz (OC Mode)/ 2520 MHz (Default Mode)
- Axial-tech fan design features a smaller fan hub that facilitates longer blades and a barrier ring that increases downward air pressure
- A 2.56-slot design maximizes compatibility and cooling efficiency for superior performance in small chassis
- 0dB technology lets you enjoy light gaming in relative silence
- Dual ball fan bearings can last up to twice as long as sleeve bearing designs
- Auto-Extreme precision automated manufacturing for higher reliability

NVIDIA GeForce RTX 4070 SUPER, 12GB GDDR6X, PCI Express 4.0, OpenGL 4.6, 21 Gbps, 192-bit, 750W, 2.56 Slot



ASUS Dual -RTX4070S-012G NVIDIA GeForce RTX 4070 SUPER 12 GB GDDR6X:

ASUS Dual GeForce RTX™ 4070 SUPER OC Edition 12GB GDDR6X with two powerful Axial-tech fans and a 2.56-slot design for broad compatibility

Processor		Ports & interfaces	
CUDA *	✓	DisplayPort version	1.4a
CUDA cores	7168 NVIDIA GeForce RTX 4070 SUPER 2520 MHz 2550 MHz 7680 x 4320 pixels	Performance	
Graphics processor family * Graphics processor * Processor boost clock speed Processor boost clock speed (OC mode) Maximum resolution *		OpenGL version * HDCP HDCP version Dual Link DVI * NVIDIA G-SYNC	4.6 ✓ 2.3 ×
Parallel processing technology	Not supported	Design	
support * Maximum displays per videocard	4	Cooling type * Cooling technology	Active ASUS Axial-tech
Memory		Number of fans	2 fan(s)
Discrete graphics card memory * Graphics card memory type * Memory bus * Memory bandwidth (max)	12 GB GDDR6X 192 bit 21 GB/s	Form factor Number of slots Product colour Power	Full-Height/Full-Length (FH/FL) 2.56 Multicolour
Ports & interfaces		Minimum system power supply *	750 W
Interface type *	ports quantity * 1 version 2.1a	Supplementary power connectors	1x 16-pin
HDMI ports quantity *		Weight & dimensions	
HDMI version DisplayPorts quantity *		Depth Height Width	51.1 mm 133.9 mm 267 mm
		Packaging data	





4711387438947

0197105442962



197105442962

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.