## ASUS ROG -STRIX-RTX4070S-12G-GAMING NVIDIA GEForce RTX 4070 SUPER 12 GB GDDR6X

Brand : ASUS Product family: ROG Product code: 90YV0KD1-M0NA00

**Product name :** ROG-STRIX-RTX4070S-12G-GAMING

- Powered by NVIDIA DLSS3, ultra-efficient Ada Lovelace arch, and full ray tracing
- 4th Generation Tensor Cores: Up to 4x performance with DLSS 3 vs. brute-force rendering
- 3rd Generation RT Cores: Up to 2x ray tracing performance
- Axial-tech fans scaled up for 31% more airflow
- 3.12-slot design: massive fin array optimized for airflow from the three Axial-tech fans
- Diecast shroud, frame, and backplate add rigidity and are vented to further maximize airflow and heat dissipation
- Digital power control with high-current power stages and 15K capacitors to fuel maximum performance
- Auto-Extreme precision automated manufacturing for higher reliability
- GPU Tweak III software provides intuitive performance tweaking, thermal controls, and system monitoring

ROG Strix GeForce RTX 4070 SUPER 12GB GDDR6X with DLSS 3 and chart-topping thermal performance.





Processor		Performance	
CUDA * CUDA cores Graphics processor family * Graphics processor * Processor boost clock speed Processor boost clock speed (OC mode) Maximum resolution *	7168 NVIDIA GeForce RTX 4070 SUPER 2475 MHz 2505 MHz 7680 x 4320 pixels	TV tuner integrated * DirectX version * OpenGL version * HDCP HDCP version Dual Link DVI * NVIDIA G-SYNC NVIDIA Ansel	12 Ultimate 4.6   2.3
Parallel processing technology support *  Maximum displays per videocard	Not supported	Design Cooling type *	Active
Memory Discrete graphics card memory * Graphics card memory type * Memory bus * Data transfer rate	12 GB GDDR6X 192 bit 21 Gbit/s	Number of fans Form factor Number of slots Illumination Illumination colour Product colour	3 fan(s) Full-Height/Full-Length (FH/FL) 3.12  ✓ Multi Multicolour
Ports & interfaces Interface type * HDMI ports quantity * HDMI version DisplayPorts quantity * DisplayPort version	PCI Express 4.0 2 2.1a 3 1.4a	Power  Minimum system power supply * Supplementary power connectors  Weight & dimensions  Depth Height Width	750 W 1x 16-pin 338.9 mm 62.4 mm 149.4 mm
		Packaging data Package type	Box



4711387465288

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.