ASUS ProArt -RTX4070S-012G NVIDIA GeForce RTX 4070 SUPER 12 GB GDDR6X

Brand : ASUS **Product family:** ProArt **Product code:** 90YV0KC4-M0NA00

Product name : PROART-

RTX4070S-O12G



- NVIDIA Studio: RTX and Al-accelerated creator apps, exclusive Al software, and Studio Drivers for unmatched creativity and performance
- NVIDIA Ada Lovelace Streaming Multiprocessors: Up to 2x performance and power efficiency
- 4th Generation Tensor Cores: Up to 4x performance with DLSS 3 vs. brute-force rendering
- OC Edition: 2565 MHz (OC mode)/ 2535 MHz (Default mode)
- 3rd Generation RT Cores: Up to 2x ray tracing performance
- Axial-tech fans scaled up for 21% more airflow
- 2.5-slot design: allows for greater build compatibility while maintaining premium cooling
- Dual Ball Fan Bearings last up to twice as long as conventional designs
- Auto-Extreme precision automated manufacturing for higher reliability
- GPU Tweak III profile Connect enables creators to seamlessly optimize system performance and cooling for every app

NVIDIA GeForce RTX 4070 SUPER 12GB GDDR6X, PCI Express 4.0, OpenGL 4.6, 21 Gbps, 192-bit, 750W, 1×16 -pin, 2.5 Slot



Processor		Performance	
CUDA * CUDA cores Graphics processor family * Graphics processor * Processor boost clock speed	✓ 7168 NVIDIA GeForce RTX 4070 SUPER 2535 MHz	HDCP HDCP version Dual Link DVI * NVIDIA G-SYNC	✓ 2.3 × ✓
Processor boost clock speed (OC mode) Maximum resolution * Parallel processing technology support * Maximum displays per videocard	2565 MHz 7680 x 4320 pixels Not supported	Cooling type * Cooling technology Number of fans Number of slots Product colour	Active ASUS Axial-tech 3 fan(s) 2.5 Black
Memory		Power	
Discrete graphics card memory * Graphics card memory type * Memory bus * Memory bandwidth (max)	12 GB GDDR6X 192 bit 21 GB/s	Minimum system power supply * Supplementary power connectors System requirements	750 W 1x 16-pin
Ports & interfaces	21 00/3	Windows operating systems supported	✓
Interface type * HDMI ports quantity * HDMI version DisplayPorts quantity * DisplayPort version	PCI Express 4.0 1 2.1a 3 1.4a	Weight & dimensions Weight Depth Height Width	992 g 50 mm 120 mm 300 mm
Performance		Packaging data	
OpenGL version * Virtual Reality (VR) ready	4.6 ✓	Package width Package depth Package height Package weight Package type	405 mm 88.5 mm 233 mm 1.68 kg Box





4711387513170

0197105513181



197105513181

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.