

Lexmark 2590+ dot matrix printer 360 x 360 DPI 556 cps

Brand : Lexmark
Product code: 11C2841
Product name : 2590+



24-pin dot matrix, 360 x 360, 12500 POH, 512 KB, 55 dBA, 8 kg, white
Lexmark 2590+. Maximum print speed: 556 cps, Maximum resolution: 360 x 360 DPI, Maximum print speed (draft): 480 cps. Cut sheet width range: 76 - 297 mm, Cut sheet length range: 76 - 559 mm, Continuous paper width range: 76 - 254 mm. Product colour: White, Buffer size: 512 KB, Sound pressure level (printing): 55 dB. Standard interfaces: Parallel, USB 2.0, Optional connectivity: Ethernet, Serial (RS-232). Print head: 24-pin, Print head life: 300 million characters, Ribbon life: 8 million characters

Printing		Endurance	
Maximum resolution *	360 x 360 DPI	Print head *	24-pin
Maximum printing width (columns) *	254	Print head life	300 million characters
Colour *	✗	Ribbon life	8 million characters
Maximum print speed *	556 cps	Mean time between failures (MTBF)	12500 h
Maximum print speed (draft)	480 cps	Operational conditions	
Maximum print speed (LQ)	160 cps	Operating temperature (T-T)	10 - 40 °C
Character pitch	10,12,15,17.1,20,24 cpi	Operating relative humidity (H-H)	8 - 90%
Line spacing	20.3 cm	System requirements	
Built-in barcodes	CODABAR (NW-7), Code 39, EAN13, EAN8, Industrial 2/5, Interleaved 2/5, POSTNET, UPC-A, UPC-E	Windows operating systems supported	✓
		Linux operating systems supported	✓
Paper handling		Server operating systems supported	Windows Server 2003, Windows Server 2003 x64, Windows Server 2008, Windows Server 2008 R2, Windows Server 2008 x64
Cut sheet width range	76 - 297 mm	Weight & dimensions	
Cut sheet length range	76 - 559 mm	Width	492 mm
Continuous paper width range	76 - 254 mm	Depth	290 mm
Continuous paper length range	76 - 559 mm	Height	195 mm
Features		Weight	8 kg
Product colour *	White	Packaging data	
Buffer size *	512 KB	Package width	609 mm
Sound pressure level (printing) *	55 dB	Package depth	408 mm
Page description languages *	Epson ESC/P2, Epson FX, PPDS	Package height	325 mm
Noise level (idle)	15 dB	Package weight	10.3 kg
Certification	UL 60950-1, CSA, FCC Class B, CB IEC 60950-1, SEMKO, GS (TÜV), CE Class B, SMA C-Tick	Other features	
		Connectivity technology	Wired
Ports & interfaces		Print technology	Dot matrix
Standard interfaces *	Parallel, USB 2.0	Network ready	✗
Optional connectivity	Ethernet, Serial (RS-232)		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-APR-2024. Prints or copies of Information are only valid on the printed Publication date