

# Epson WorkForce DS-6500N Flatbed scanner 1200 x 1200 DPI A4 White

**Brand :** Epson

**Product code:** B11B205231BU

**Product name :** WorkForce DS-6500N



WorkForce DS-6500N, 1200 dpi x 1200 dpi, Flatbed, ReadyScan LED, 3000 ppm, Mono: 25 p/min -

Colour: 25 p/min, Ethernet

Epson WorkForce DS-6500N. Maximum scan size: 215.9 x 1.016 mm, Optical scanning resolution: 1200 x 1200 DPI, Input colour depth: 48 bit. Scanner type: Flatbed scanner, Product colour: White, Display: LCD.

Daily duty cycle (max): 3000 pages, Light source: ReadyScan LED, Scan file formats: JPG, PDF, TIFF.

Standard input capacity: 100 sheets. Maximum ISO A-series paper size: A4, Scanning media types supported: Envelopes, Plain paper, Thin paper, Transparencies, ISO A-series sizes (A0...A9): A4



| Scanning                                |  | Network                             |  |                                    |  |                                 |             |
|---|--|-------------------------------------|--|------------------------------------|--|---------------------------------|-------------|
| Maximum scan size *                     | 215.9 x 1.016 mm                                   | Supported network protocols         | TCP/IP, DHCP, DNS, SNMP, SLP, HTTP   |                                    |  |                                 |             |
| Optical scanning resolution *           | 1200 x 1200 DPI                                    |                                     |  |                                    |  |                                 |             |
| Colour scanning                         | ✓  |                                     |  |                                    |  |                                 |             |
| Duplex scanning *                       | ✓  |                                     |  |                                    |  |                                 |             |
| Input colour depth                      | 48 bit   |                                     |  |                                    |  |                                 |             |
| Output colour depth                     | 24 bit   |                                     |  |                                    |  |                                 |             |
| Film scanning                           | ✗  |                                     |  |                                    |  |                                 |             |
| ADF scan speed (b/w, A4)                | 25 ppm   |                                     |  |                                    |  |                                 |             |
| ADF scan speed (colour, A4)             | 25 ppm   |                                     |  |                                    |  |                                 |             |
| Duplex ADF scan speed (b/w, A4)         | 50 ipm   |                                     |  |                                    |  |                                 |             |
| Duplex ADF scan speed (colour, A4)      | 50 ipm   |                                     |  |                                    |  |                                 |             |
| Design                                  |  | Features                            |  |                                    |  |                                 |             |
| Scanner type *                          | Flatbed scanner                                    | Country of origin                   | China  |                                    |  |                                 |             |
| Product colour *                        | White  |                                     |  |                                    |  |                                 |             |
| Display                                 | LCD  |                                     |  |                                    |  |                                 |             |
| Built-in display *                      | ✓  |                                     |  |                                    |  |                                 |             |
| Performance                             |  |                                     |  | Packaging data                     |  |                                 |             |
| Light source                            | ReadyScan LED                                      |                                     |  | Quantity per pack                  | 1 pc(s)  |                                 |             |
| Scan file formats                       | JPG, PDF, TIFF                                     |                                     |  |                                    |  |                                 |             |
| Daily duty cycle (max) *                | 3000 pages   |                                     |  |                                    |  |                                 |             |
| Scan drivers                            | ISIS, TWAIN, WIA                                   |                                     |  |                                    |  |                                 |             |
| Input capacity                          |  |                                     |  |                                    |  | System requirements             |             |
| Standard input capacity                 | 100 sheets   | Windows operating systems supported | Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64 |                                    |  |                                 |             |
| Paper handling                          |  |                                     |  |                                    |  | Mac operating systems supported | ✓           |
| Scanning media types supported          | Envelopes, Plain paper, Thin paper, Transparencies |                                     |  |                                    |  |                                 |             |
| Maximum ISO A-series paper size *       | A4   |                                     |  |                                    |  |                                 |             |
| ISO A-series sizes (A0...A9)            | A4   |                                     |  |                                    |  |                                 |             |
| ISO B-series sizes (B0...B9)            | B5   |                                     |  |                                    |  |                                 |             |
| Letter                                  | ✓  |                                     |  |                                    |  |                                 |             |
| Legal                                   | ✓  |                                     |  |                                    |  |                                 |             |
| Auto Document Feeder (ADF) media weight | 50 - 128 g/m²                                      |                                     |  |                                    |  |                                 |             |
| Ports & interfaces                      |  |                                     |  | Server operating systems supported | Windows Server 2003, Windows Server 2008, Windows Server 2008 R2 |                                 |             |
| Standard interfaces                     | Ethernet   |                                     |  |                                    |  |                                 |             |
| Power                                   |  | Operational conditions              |  |                                    |  |                                 |             |
| Power supply type *                     | AC   | Operating temperature (T-T)         | 5 - 35 °C  |                                    |  |                                 |             |
| Power consumption (typical)             | 19 W   |                                     |  |                                    |  |                                 |             |
| Power consumption (standby)             | 4.8 W  |                                     |  |                                    |  |                                 |             |
| Power consumption (PowerSave)           | 15.5 W   |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  | Storage temperature (T-T)       | -25 - 60 °C |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  | Operating relative humidity (H-H)   | 10 - 80%   |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  | Storage relative humidity (H-H)     | 10 - 85%   |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  | Weight & dimensions                 |  |                                    |  |                                 |             |
|   |  | Width                               | 495 mm   |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  | Depth                               | 360 mm   |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |
|   |  |                                     |  |                                    |  |                                 |             |

| Power                          |            | Weight & dimensions |   |
|--------------------------------|------------|---------------------|---|
| AC input frequency             | 50 - 60 Hz | Height              | 217 mm  |
| Input voltage                  | 220-240 V  | Weight              | 10.3 kg   |
| Network                        |            | Packaging content   |   |
| Ethernet LAN                   | ✓          | Drivers included    | ✓   |
|                                |            | Bundled software    | ABBYY FineReader® Sprint 8.0 (MacOS), ABBYY FineReader® Sprint 9.0 (Windows), Epson Document Capture Pro (Windows only), Epson Document Capture Pro Server (on free download), Epson Event Manager (Mac Only), Epson Scan |
| Technical details              |            |                     |   |
| Sustainability certificates    |            | ENERGY STAR         |   |
| Harmonized System (HS) code    |            | 84716070            |   |
| Logistics data                 |            |                     |   |
| Products per pallet            |            | 12 pc(s)            |   |
| Pallet gross length            |            | 120 cm              |   |
| Pallet gross width             |            | 80 cm               |   |
| Pallet gross height            |            | 157.8 cm            |   |
| Products per pallet layer      |            | 2 pc(s)             |   |
| Products per pallet layer (UK) |            | 4 pc(s)             |   |
| Products per pallet (UK)       |            | 24 pc(s)            |   |
| Pallet length (UK)             |            | 120 cm              |   |
| Pallet width (UK)              |            | 100 cm              |   |
| Pallet height (UK)             |            | 157.8 cm            |   |



8715946510880

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 17-JAN-2023. Prints or copies of Information are only valid on the printed Publication date