



Eaton 9PX6KIRTN uninterruptible power supply (UPS) Double-conversion (Online) 6 kVA 5400 W 11 AC outlet(s)



Brand : Eaton

Product code: 9PX6KIRTN

Product name : 9PX6KIRTN

9PX with Network Card and Rack Kit, 6000VA

Eaton 9PX6KIRTN uninterruptible power supply (UPS) Double-conversion (Online) 6 kVA 5400 W 11 AC outlet(s):



The Eaton 9PX UPS provides energy-efficient power protection for small & medium Datacentres, IT rooms and Infrastructure. Delivering double conversion protection with 40% less energy usage and 28% more power 9PX is the perfect UPS for IT and Facility managers that are concerned by energy cost and are looking for next generation power protection solutions.

- Online double conversion topology
- Energy efficient (up to 95% in Online mode, 98% in high-efficiency mode, ENERGY STAR® qualified UPS)
- Next-generation graphical LCD display (7 languages)
- Provides more real power (watts) to protect more equipment with a 0.9 power factor
- Parallel operation using HotSync technology (available in Q2 2013)
- Maintenance ByPass available as standard (on HotSwap/BP version)
- Energy metering - kWh values can be monitored using the LCD or Eaton's Intelligent Power Software Suite
- Compatible with Virtual environments (VMware, Hyper-V, Citrix Xen, Redhat)

Features		Battery	
UPS topology *	Double-conversion (Online)	Typical backup time at half load	11 min
Output power capacity *	6 kVA	Hot-swap battery	✓
Output power *	5400 W	Automatic battery test	✓
Waveform *	Pure sine	Design	
Input operation voltage (min) *	176 V	Form factor *	Rackmount/Tower
Input operation voltage (max) *	276 V	Rack capacity	3U
Input frequency *	40/70 Hz	Product colour *	Black
Output operation voltage (min)	200 V	Display type	LCD
Output operation voltage (max)	240 V	LED indicators	✓
Output frequency	50/60 Hz	Safety	IEC/EN 62040-1, UL 1778
Number of input phases	1	Certification	IEC/EN 62040-1, UL 1778, IEC/EN 62040 -2, FCC Class A, IEC/EN 62040-3 (Performance), CE, CB report (TUV), UL
Efficiency	94%		
Power factor	0.9	Operational conditions	
Crest factor	3:1	Operating temperature (T-T)	0 - 40 °C
Output voltage Total Harmonic Distortion (THD)	2%	Technical details	
Input current Total Harmonic Distortion (THD)	5%	Sustainability certificates	ENERGY STAR
Noise level	45 dB	Harmonized System (HS) code	85078000
Ports & interfaces		Weight & dimensions	
AC outlet types	C13 coupler, C19 coupler, Terminal	Width	440 mm
Power plug	Terminal	Depth	685 mm
AC outlets quantity	11 AC outlet(s)	Height	130 mm
USB port	✓	Weight	48 kg
USB 2.0 ports quantity	1	Packaging data	
RS-232 ports	1	Rack mount kit	✓
Battery		Management card included	✓
Battery technology	Sealed Lead Acid (VRLA)	Bundled software	Intelligent Power Software suite
		Other features	
		Interface	USB, RS232

Other features

Nominal output voltage	230 V
Nominal input voltage	230 V



0743172040190



743172040190

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.