

## POLY VVX 600 DECT telephone Black, White

**Brand : POLY** Product code: 2200-44600-025

**Product name:** VVX 600

VVX600, Large (4.3") TFT (480 x 272) capacitive touch-screen, Up to 16 line appearances/speed dials, Hard Keys: 12-key keypad, home, speaker, mute, volume, headset, Video playback and video conferencing via external USB cam

POLY VVX 600. Type: DECT telephone. Speakerphone. Display diagonal: 10.9 cm (4.3"). Product colour: Black, White





Performance		Display	
Type * Answering machine *	DECT telephone  ✓	Touchscreen type Display number of colours	Capacitive 16.78 million colours
Intercom	<b>√</b>	Ports & interfaces	
Ringer type	MP3	USB 2.0 ports quantity	2
Design	Deel	Wireless connection	<b>V</b>
Mounting type *  Product colour *	Desk Black, White	DC-in jack	✓
Big buttons	✓	Network	
Backlight buttons	✓	Bluetooth version	2.1+EDR
Phone features		Operational conditions	
Speakerphone *	✓	Operating temperature (T-T)	0 - 40 °C
Microphone mute	✓	Storage temperature (T-T) Operating relative humidity (H-H)	-40 - 70 °C 5 - 95%
Noise reduction	×	, ,	3 - 9370
Call management		Certificates	
Caller ID * Conference call Call waiting Caller ID on call waiting Call hold Call timer	<b>X</b>	Certification	- Argentina CNC - South Africa ICASA - Saudi Arabia CITC - India TEC - Japan MIC/VCCI Class B - Malaysia SIRIM - Israel MOC - Singapore IDA - Taiwan NCC3 - Mexico NOM-121 - FCC Part 15 (CFR 47) Class B - ICES-003 Class B - EN55022 Class B - CISPR22 Class B - VCCI Class B - EN55024 -
Management features			EN61000-3-2; EN61000-3-3 - NZ
Navigation key Alarm clock Calendar	√ √		Telepermit - Korea KC - UAE TRA - Russia GOST-R - Brazil ANATEL3 - Australia A&C Tick - ROHS compliant - China CCC3
Programmable hot keys	✓	Weight & dimensions	
Indication		Width	210 mm
LED indicators	✓	Depth	150 mm
Display		Height	180 mm
Display	LED	Weight	900 g
Display diagonal	10.9 cm (4.3")	Packaging content	
Display resolution	480 x 272 pixels	Manual	<b>√</b>
Display number of lines	16 lines	Quick start guide Cables included	<b>√</b> USB
Brightness adjustment	1	capies included	035
Display contacts list status	✓		

Display		Logistics data	
Built-in display *	<b>✓</b>	Harmonized System (HS) code	85171800
		Other features	
		Power LED	✓
		Ethernet LAN (RJ-45) ports	2









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.