

## Lindy 10m USB 3.0 Active Extension Pro

Brand: Lindy Product code: 43157

Product name: 10m USB 3.0 Active Extension Pro

- High performance, active cable that provides an extended 10m connection between a computer and USB  $3.0\ device$
- Can be used standalone or as part of the Lindy Active Extension System Pro to create bespoke extension systems of over 40m (depending on the cable configurations used)
- Supports the full USB 3.0 SuperSpeed bandwidth for speeds of 5Gbps
- Easy to use  $\square$  connects to the deviceandrsquo;s existing USB cable (2m maximum)
- 2 year warranty

10m USB 3.0 Active Extension Pro

Lindy 10m USB 3.0 Active Extension Pro. Cable length: 10 m, Connector 1: USB A, Connector 2: USB A, USB version: USB 3.2 Gen 1 (3.1 Gen 1), Maximum data transfer rate: 5000 Mbit/s, Connector contacts plating: Gold, Product colour: Black





Features		Features	
Cable length * USB version *	10 m USB 3.2 Gen 1 (3.1 Gen 1)	Certification	CE, UKCA, FCC, RoHS, REACH, California Proposition 65
Connector 1 *	USB A	Power	·
Connector 2 *	USB A	Power note	2.5/0.7mm DC
Connector 1 gender *	Male Weight & dimensions		
Connector 2 gender *	Female	Cable diameter	7 mm
Connector 1 form factor	Straight	Bend radius (min)	3.6 cm
Connector 2 form factor	Straight	Connector 1 dimensions (WxDxH)	15 x 49 x 8 mm
AWG wire size	24/24/20	Connector 2 dimensions (WxDxH)	20 x 80 x 13 mm
Connector material	Nickel	Weight	750 g
Contact material	Brass	,	750 g
Connector contacts plating	Gold	Packaging data	
Cable jacket material	Polyvinyl chloride (PVC)	Quantity per pack *	1 pc(s)
Conductor material	Tinned copper	Package width	240 mm
Connector shielding	<b>4</b>	Package depth	70 mm
Connector shield material	Aluminium	Package height	200 mm
Connector housing material	Plastic	Package weight	900 g
Maximum data transfer rate	5000 Mbit/s	Package type	Box
Product colour *	Black	Packaging content	
Cable type	Round cable	Manual	1
Transmission medium	Twisted pair		•
Nominal attenuation	0.064MHz - 0.08dB 0.256MHz - 0.11dB 0.512MHz - 0.13dB 0.772MHz - 0.15dB 1.0MHz - 0.20dB 4MHz - 0.39dB 8MHz - 0.57dB 12MHz - 0.67dB 24MHz - 0.95dB 48MHz - 1.35dB 96MHz - 1.90dB 200MHz - 3.20dB 400MHz - 5.80dB	Operational conditions	
		Operating temperature (T-T)	0 - 50 °C
		Storage temperature (T-T)	-20 - 60 °C
		Logistics data	
		Harmonized System (HS) code	84733080



4002888431576

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.