Brother TD-2130N label printer Direct thermal 300 x 300 DPI 152.4 mm/sec Wired Ethernet LAN

Brand : Brother

**Product name :** TD-2130N

Product code: TD-2130N

300 x 300 dpi, 63mm, 16MB SDRAM, 152.4mm/sec, USB 2.0, Ethernet LAN
Brother TD-2130N. Print technology: Direct thermal, Maximum resolution: 300 x 300 DPI, Print speed: 152.4 mm/sec. Connectivity technology: Wired. Product colour: Black, Grey


Printing

Print technology *	Direct thermal
Maximum resolution *	300 x 300 DPI
Print speed *	152.4 mm/sec
Maximum printing width *	5.6 cm
Vertical printing	✔

Paper handling

Autocutter	✔
Ribbon length	1 m
Maximum label length	1 m

Ports & interfaces

Connectivity technology *	Wired
Ethernet LAN *	✔
USB port *	✔
USB 2.0 ports quantity	1
RS-232 ports	1
Optional connectivity	Bluetooth, Wireless LAN

Performance

Page description languages	ESC P
Internal memory	32 MB
Flash memory	16 MB
Built-in barcodes	2D, CODABAR (NW-7), Code 128 (A/B/C), Code 39, Data Matrix, EAN13, EAN8, GS1 DataBar, GS1-128, ITF, MaxiCode, Micro QR Code, MicroPDF417, PDF417, QR Code, UPC-A, UPC-E
Number of fonts	10
Tape cutting	Automatic
Underline	✔
Security algorithms	128-bit WEP, 64-bit WEP, EAP-TLS, EAP-TTLS, LEAP, PEAP, SSID, TKIP, WPA-PSK, WPA2-PSK

Power

AC adapter output current	6 A

System requirements

Minimum storage drive space	70 MB
Minimum RAM	128 MB
Windows operating systems supported	Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Server operating systems supported	Windows Server 2003, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012

Operational conditions

Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	20 - 80%
Operating temperature (T-T)	5 - 40 °C
Storage temperature (T-T)	-20 - 60 °C

Weight & dimensions

Width	110 mm

Design

Product colour *	Black, Grey
Display *	LCD

Power

AC adapter output voltage	25 V

Weight & dimensions

Depth	215 mm
Height	172 mm
Weight	1.34 kg

Packaging data

Package weight	2.83 kg

Packaging content

Cables included	USB
Drivers included	✓
AC adapter included	✓

Logistics data

Harmonized System (HS) code	84433210

Other features

Character sets	Abicomp, ASCII, BRASCII, ISO 8859-15, ISO Latin 1, Italic, PC437, PC850, PC858, PC860, PC861, PC863, PC865, Roman 8
LED indicators	✓

0012502634584

012502634584

4977766719711

4977766720502

5054533730120