

StarTech.com 2-Port VGA Auto Switch Box with Priority Switching and EDID Copy

Brand : StarTech.com

Product code: ST122VGA

Product name : 2-Port VGA Auto Switch Box with Priority Switching and EDID Copy

StarTech.com 2-Port VGA Auto Switch Box with Priority Switching and EDID Copy - 2x1 Dual Port Monitor VGA Switch 1920x1200

StarTech.com 2-Port VGA Auto Switch Box with Priority Switching and EDID Copy. Video port type: VGA, Video in: VGA, Video out: 2x VGA. Material: Aluminium, Product colour: Black, Supported graphics resolutions: 1366 x 768, 1600 x 900, 1920 x 1440, 2048 x 1152, 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720.... AC input voltage: 100 - 240 V, AC adapter input current: 0.4 A, AC adapter output voltage: 5 V. Certification: CE, FCC, TAA, REACH. Width: 59 mm, Depth: 74 mm, Height: 21 mm



Ports & interfaces		Weight & dimensions	
Video port type *	VGA	Width	59 mm
VGA (D-Sub) ports quantity	2	Depth	74 mm
Video in	VGA	Height	21 mm
Video out	2x VGA	Weight	170 g
DC-in jack	✓	Length	74 mm
Features		Packaging data	
Material	Aluminium	Package width	170 mm
Product colour	Black	Package depth	145 mm
Extended display identification data (EDID)	✓	Package height	66 mm
Supported graphics resolutions	1366 x 768, 1600 x 900, 1920 x 1440, 2048 x 1152, 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1440 x 900 (WXGA+), 1600 x 1200 (UXGA), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA)	Package weight	469 g
Supported video modes	1080p	Packaging content	
LED indicators	✓	Quantity per pack	1 pc(s)
Maximum resolution	2048 x 1152 pixels	Manual	✓
External power adapter	✓	Cables included	USB
Power		Plug adapter type	NA, EU, UK, ANZ
AC input voltage	100 - 240 V	Operational conditions	
AC adapter input current	0.4 A	Operating temperature (T-T)	0 - 40 °C
AC adapter output voltage	5 V	Storage temperature (T-T)	-10 - 60 °C
AC adapter output current	2 A	Operating relative humidity (H-H)	0 - 80%
Power consumption (typical)	10 W	Sustainability	
Certificates		Sustainability certificates	RoHS
Certification	CE, FCC, TAA, REACH	Technical details	
		Harmonized System (HS) code	85176990



0065030852821



065030852821



0195870085445



195870085445

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.