iiyama

iiyama ProLite XU2390HS 58.4 cm (23") 1920 x 1080 pixels Full HD LED Black

Brand : iiyama
Product family: ProLite
Product code: XU2390HS-B1

Product name : XU2390HS

23" IPS LED, 1920x1080, 16:9, 250cd/m², 5ms, 16.7M, 2x2W RMS, VGA, DVI-D, HDMI, 24W, 4kg, Black
iiyama ProLite XU2390HS. Display diagonal: 58.4 cm (23"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LED. Display: LED. Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). VESA mounting. Product colour: Black

Display	
Display diagonal *	58.4 cm (23")
Display resolution *	1920 x 1080 pixels
HD type *	Full HD
Native aspect ratio *	16:9
Display technology *	LED
Panel type *	IPS
Touchscreen *	✗
Display brightness (typical)	250 cd/m²
Response time	4 ms
Screen shape *	Flat
Supported graphics resolutions	1920 x 1080 (HD 1080)
Supported video modes	1080p
Aspect ratio	16:9
Contrast ratio (typical) *	1000:1
Contrast ratio (dynamic)	5000000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.7 million colours
Pixel pitch	0.265 x 0.265 mm
Horizontal scan range	24 - 80 kHz
Vertical scan range	56 - 75 Hz
Viewable size, horizontal	50.9 cm
Viewable size, vertical	28.6 cm
Viewable size diagonal	58.4 cm
3D	✗
Separate H/V sync	✓

Ergonomics	
Cable lock slot *	✓
Cable lock slot type	Kensington
Height adjustment *	✗
Pivot	✗
Swivelling	✗
Tilt angle range	-4 - 20°
On Screen Display (OSD)	✓
On Screen Display (OSD) languages	Simplified Chinese, English, Spanish, French, Italian, Japanese, Portuguese, Russian
Number of OSD languages	9
Plug and Play	✓
Tilt adjustment	✓

Power	
Energy efficiency class (SDR) *	E
Energy consumption (SDR) per 1000 hours *	16 kWh
Power consumption (typical) *	24 W
Power consumption (standby) *	0.5 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Energy efficiency scale	A to G

Operational conditions	
Operating temperature (T-T)	5 - 35 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 80%
Storage relative humidity (H-H)	5 - 85%

Packaging content	
Stand included	✓
Cables included	AC, Audio (3.5mm), DVI
Quick start guide	✓

Performance

Windows operating systems supported	Windows 2000, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 95, Windows 98, Windows ME, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64

Multimedia

Built-in speaker(s) *	✔
Built-in camera *	✘
Number of speakers	2
RMS rated power	4 W

Design

Market positioning *	Business
Product colour *	Black
Certification	TCO, CE, TÜV-Bauart, VCCI-B, EAC

Ports & interfaces

VGA (D-Sub) ports quantity	1
DVI port	✔
DVI-D ports quantity	1
HDMI ports quantity	1
Audio input	✔
HDCP	✔
AC (power) in	✔

Ergonomics

VESA mounting *	✔
Panel mounting interface	100 x 100 mm

Weight & dimensions

Width (with stand)	532.5 mm
Depth (with stand)	180 mm
Height (with stand)	387.5 mm
Weight (with stand)	4 kg
Width (without stand)	53.2 cm
Depth (without stand)	4.4 cm
Height (without stand)	31.8 cm

Sustainability

Sustainability certificates	EPEAT Silver, ENERGY STAR

Logistics data

Harmonized System (HS) code	85285210

Thin Client

Thin client installed	✘

Other features

Display	LED
On/off switch	✔
TV tuner integrated	✘

4948570112982