

iiyama ProLite B1780SD LED display 43.2 cm (17") 1280 x 1024 pixels White

Brand : iiyama

Product family: ProLite

Product code: B1780SD-W1

Product name : B1780SD

17" TN LED, 1280x1024, 5:4, 250cd/m², 5ms, 16.7M, 2x1W RMS, VGA, DVI-D, 14W, 4.4kg, White
 iiyama ProLite B1780SD. Display diagonal: 43.2 cm (17"), Display resolution: 1280 x 1024 pixels, Display technology: LED. Display: LED. Display surface: Matt, Response time: 5 ms, Native aspect ratio: 5:4, Viewing angle, horizontal: 170°, Viewing angle, vertical: 160°. Built-in speaker(s). VESA mounting, Height adjustment. Product colour: White



Display		Ergonomics	
Display diagonal *	43.2 cm (17")	Cable lock slot *	✓
Display resolution *	1280 x 1024 pixels	Cable lock slot type	Kensington
HD type *	Not supported	Height adjustment *	✓
Native aspect ratio *	5:4	Height adjustment	13 cm
Display technology *	LED	Pivot	✓
Panel type *	TN	Pivot angle	0 - 90°
Touchscreen *	✗	Swivelling	✓
Display brightness (typical)	250 cd/m ²	Swivel angle range	-45 - 45°
Response time	5 ms	Tilt angle range	-3 - 22°
Display surface	Matt	On Screen Display (OSD)	✓
Screen shape *	Flat	On Screen Display (OSD) languages	Simplified Chinese, German, Dutch, English, French, Japanese, Polish, Russian
Supported graphics resolutions	1280 x 1024 (SXGA)	Number of OSD languages	9
Aspect ratio	5:4	Plug and Play	✓
Contrast ratio (typical) *	1000:1	Power	
Contrast ratio (dynamic)	12000000:1	Energy efficiency class (SDR) *	E
Viewing angle, horizontal	170°	Energy consumption (SDR) per 1000 hours *	12 kWh
Viewing angle, vertical	160°	Power consumption (typical) *	14 W
Display number of colours *	16.78 million colours	Power consumption (standby) *	0.5 W
Pixel pitch	0.264 x 0.264 mm	AC input voltage	100 - 240 V
Horizontal scan range	24 - 80 kHz	AC input frequency	50 - 60 Hz
Vertical scan range	55 - 75 Hz	Energy efficiency scale	A to G
Viewable size, horizontal	33.8 cm	Operational conditions	
Viewable size, vertical	27 cm	Operating temperature (T-T)	5 - 35 °C
Viewable size diagonal	43.2 cm	Storage temperature (T-T)	-20 - 60 °C
3D	✗	Operating relative humidity (H-H)	10 - 80%
Separate H/V sync	✓	Storage relative humidity (H-H)	5 - 85%
Performance		Packaging content	
NVIDIA G-SYNC *	✗	Stand included	✓
AMD FreeSync *	✗	Cables included	AC, Audio (3.5mm), DVI, VGA
		Quick start guide	✓
		Weight & dimensions	
		Width (with stand)	370 mm
		Depth (with stand)	230 mm

Performance		Weight & dimensions	
Windows operating systems supported	Windows 2000, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8, Windows 95, Windows 98, Windows ME, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64	Height (with stand)	399.5 mm
		Weight (with stand)	4.4 kg
		Width (without stand)	370 mm
		Depth (without stand)	48.5 mm
		Height (without stand)	322 mm
Sustainability		Sustainability certificates	EPEAT Silver, ENERGY STAR
Logistics data		Harmonized System (HS) code	85285210
Thin Client		Thin client installed	✗
Other features		Display	LED
		On/off switch	✓
		Built-in subwoofer	✗
		TV tuner integrated	✗
Mac operating systems supported	✓		
Multimedia		Built-in speaker(s) *	✓
		Built-in camera *	✗
		Number of speakers	2
		RMS rated power	2 W
Design		Market positioning *	Business
		Product colour *	White
		Certification	CE, TÜV-Bauart, VCCI-B, TCO, GOST-R
Ports & interfaces		Built-in USB hub *	✗
		VGA (D-Sub) ports quantity	1
		DVI port	✓
		DVI-D ports quantity	1
		PC Audio in	✓
		HDCP	✓
		AC (power) in	✓
Ergonomics		VESA mounting *	✓
		Panel mounting interface	100 x 100 mm



4948570113095

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-SEP-2023. Prints or copies of Information are only valid on the printed Publication date