FAT•N

Eaton EMIB04 power distribution unit (PDU) 24 AC outlet(s) 0U **Black**

Product code: EMIB04 **Brand**: Eaton

Product name: EMIB04

ePDU G3 Metered Input, 4kW, 230V In, 1 x 60309 16A In, 20 x C13 & 4 x C19 Out

Eaton EMIB04 power distribution unit (PDU) 24 AC outlet(s) 0U Black:

New ePDU G3 Metered Input models feature best-in-class technologies, including ±1% billing grade accuracy, an advanced LCD pixel display, a hot-swap meter and the ability to daisy chain four ePDUs to share the same network connection and IP address.

Eaton EMIB04. PDU types: Metered, Rack capacity: 0U, Type: Single-phase. AC outlets quantity: 24 AC outlet(s), AC outlet types: C13 coupler, C19 coupler, Power plug: IEC 60309. Cable length: 3 m. Management protocols: SNMP, Telnet, Firmware upgradeable via: Network, USB. Nominal input voltage: 230 V, Maximum current: 16 A, AC input frequency: 50 Hz



| Design | | Power | |
|--|-----------------------------------|---|---|
| PDU types * Metered Type Single-phase Form factor Rackmount Rack mounting Rack capacity * OU Mounting Vertical | Single-phase Rackmount ✓ 0U | Nominal input voltage * AC input frequency Maximum current * Nominal output voltage Maximum input current per phase Maximum power | 230 V 50 Hz 16 A 230 V 16 A 3700 W |
| Product colour | Black | Weight & dimensions | |
| Cable colour Display | Black LCD | Width Depth | 52 mm 1070 mm |
| Ports & interfaces | | Dimensions (WxDxH) | 52 x 1070 x 53 mm |
| AC outlets quantity * Power plug | 24 AC outlet(s) IEC 60309 | Height Weight | 53 mm 2.98 kg |
| AC outlet types * | C13 coupler, C19 coupler | Packaging data | |
| Ethernet LAN (RJ-45) ports Output connections | 1 20 x C13 & 4 x C19 | Package weight | 3.98 kg |
| Features | 20 % 023 4 . % 023 | Packaging content | |
| LED indicators Cable length | √ 3 m | Cables included Rack mount kit | LAN (RJ-45) ✓ |
| Management features | | Operational conditions | |
| Management protocols | SNMP, Telnet | Operating temperature (T-T) | 0 - 60 °C |
| Firmware upgradeable | ✓ | Technical details | |
| Firmware upgradeable via | Network, USB | Sustainability certificates | RoHS |





743172065896

0743172065896

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.