## ZYXEL

## Zyxel GS1900-48HP Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Black

**Brand :** Zyxel **Product code:** GS1900-48HP-GB0101F

Product name: GS1900-48HP

48-port GbE Smart Managed PoE Switch with GbE Uplink

Zyxel GS1900-48HP. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. MAC address table: 8000 entries, Switching capacity: 100 Gbit/s. Networking standards: IEEE 802.1af, IEEE 802.1D, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Power connector: DC-in jack. Power over Ethernet (PoE). Rack mounting, Form factor: 1U





Management features		Power	
Switch type * Switch layer	Managed L2	AC input voltage AC input frequency	100 - 240 V 50 - 60 Hz
Ports & interfaces		Power consumption (typical)	250 W
Basic switching RJ-45 Ethernet ports	24	Power over Ethernet (PoE)	
quantity * Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power over Ethernet (PoE) * Power over Ethernet plus (PoE+) ports quantity	24
SFP module slots quantity Power connector	2 DC-in jack	Total Power over Ethernet (PoE) budget	170 W
Network		Operational conditions	
Networking standards *  10G support *	IEEE 802.1af, IEEE 802.1D, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Heat dissipation	0 - 50 °C -40 - 70 °C 10 - 95% 853 BTU/h
Data transmission		Weight & dimensions	
Switching capacity * Throughput MAC address table * Packet buffer memory	100 Gbit/s 74 Mpps 8000 entries 1.5 MB	Width Depth Height Weight	440 mm 200 mm 44 mm 29 kg
Design		Packaging data	
Rack mounting * Form factor Product colour LED indicators	√ 1U Black √	Package width Package depth Package height Package weight	583 mm 451 mm 98 mm 5.31 kg
Performance		Logistics data	
Mean time between failures (MTBF)	175767 h	Harmonized System (HS) code	85176990

