CyberPower CP900EPFCLCD-UK uninterruptible power supply (UPS) Line-Interactive 0.9 kVA 540 W 6 AC outlet(s)

Brand : CyberPower

Product code: CP900EPFCLCD-UK

Product name : CP900EPFCLCD-UK

Nominal 230 V, 10 A, Cord 1.83 m, 100 x 275 x 230 mm, 6.6 kg, 0 - 40°C CyberPower CP900EPFCLCD-UK. UPS topology: Line-Interactive, Output power capacity: 0.9 kVA, Output power: 540 W. AC outlet types: C13 coupler, Type G (BS 1363), Power plug: C14 coupler, AC outlets quantity: 6 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery voltage: 230 V, Typical backup time at full load: 1 min. Form factor: Tower, Product colour: Black, Housing material: Plastic. Width: 100 mm, Depth: 275 mm, Height: 230 mm





Features		Battery	
UPS topology * Output power capacity * Output power * Waveform *	540 W Sine 170 V 270 V 50/60 Hz 50/60 Hz R) ✓ 10 A 405 J	Number of batteries supported Typical backup time at full load Typical backup time at half load Battery recharge time	1 1 min 7 min 8 h
Input operation voltage (min) * Input operation voltage (max) * Input frequency * Output frequency Automatic Voltage Regulation (AVR) Maximum current Surge energy rating Output voltage Total Harmonic Distortion (THD)		Design Form factor * Housing material Cable length Product colour * Display type LED indicators Certification	Tower Plastic 1.83 m Black LCD Power CE, EAC, RCM
EMI/RFI noise filtering Surge protection Surge protection features Power protection features Audible alarm(s) Audible alarm modes	 Fax, Modem, Network, Telephone Over current Alarm when on battery, Low battery alarm, Overload alarm 	Operational conditions Operating temperature (T-T) Operating relative humidity (H-H) Operating altitude Technical details Sustainability certificates	0 - 40 °C 0 - 95% 0 - 300 m RoHS
Auto-restart Ports & interfaces AC outlet types Power plug AC outlets quantity USB 2.0 ports quantity Modem (RJ-11) ports	 C13 coupler, Type G (BS 1363) C14 coupler 6 AC outlet(s) 1 2 	Weight & dimensions Width Depth Height Weight Package width Package depth	100 mm 275 mm 230 mm 6.6 kg 195 mm 365 mm
Battery Battery technology Battery voltage	Sealed Lead Acid (VRLA) 230 V	Package height Package weight Other features Suitable for use in country/location	335 mm 7.8 kg United Kingdom



4712364146244

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.