



APC AP8459EU3 power distribution unit (PDU) 24 AC outlet(s) 0U Black

Brand : APC

Product code: AP8459EU3

Product name : AP8459EU3

Metered-by-Outlet Rack PDU 2G, 230V, 21 x C13 & 3 x C19 Out, IEC 309 16A 2P+E In, 0U

[APC AP8459EU3 power distribution unit \(PDU\) 24 AC outlet\(s\) 0U Black:](#)

Metering-by-Outlet capability

Individual outlet level power metering provides a more granular view of the power distributed to equipment within the enclosure. It also provides the ability to analyze component power trends and perform capacity planning.

APC AP8459EU3. PDU types: Metered, Metered-by-outlet, Rack capacity: 0U, Mounting: Vertical. AC outlets quantity: 24 AC outlet(s), AC outlet types: C13 coupler, C19 coupler, Power plug: IEC309. Cable length: 3 m, Certification: EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Class A, ICES-003, UL Listed,.... Monitoring: Current, Power, Voltage. Nominal input voltage: 200-230 V, Maximum current: 16 A, AC input frequency: 50 - 60 Hz



Design		Power	
PDU types *	Metered, Metered-by-outlet	Load capacity	3680 VA
Rack capacity *	0U	Maximum input current per phase	16 A
Mounting	Vertical	Maximum total current draw per phase	16 A
Product colour	Black	Maximum power	3680 W
Ports & interfaces		Weight & dimensions	
AC outlets quantity *	24 AC outlet(s)	Dimensions (WxDxH)	56 x 51 x 1829 mm
Power plug	IEC309	Weight	6.76 kg
AC outlet types *	C13 coupler, C19 coupler	Packaging data	
Output connections	21 x C13 & 3 x C19	Package dimensions (WxDxH)	163 x 117 x 2037 mm
Features		Package weight	9.03 kg
LED indicators	✓	Operational conditions	
Cable length	3 m	Operating temperature (T-T)	-5 - 45 °C
Certification	EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Class A, ICES-003, UL Listed, VCCI Class A, VDE REACH	Storage temperature (T-T)	-25 - 65 °C
		Operating relative humidity (H-H)	5 - 95%
Management features		Storage relative humidity (H-H)	5 - 95%
Monitoring	Current, Power, Voltage	Operating altitude	0 - 3000 m
Power		Non-operating altitude	0 - 15000 m
Nominal input voltage *	200-230 V	Technical details	
AC input frequency	50 - 60 Hz	Sustainability certificates	RoHS
Maximum current *	16 A		
Nominal output voltage	230 V		



0731304317562



731304317562

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.