## Brother HL-1210W laser printer 2400 x 600 DPI A4 Wi-Fi

Brand : Brother

Product code: HL-1210W

Product name : HL-1210W


HL-1210W - A4, 20ppm, 2400x600 dpi, USB 2.0, GDI, 32MB, 4.6 kg Brother HL-1210W. Print technology: Laser. Number of print cartridges: 1. Maximum resolution: 2400 x 600 DPI. Maximum ISO A-series paper size: A4. Print speed (black, normal quality, A4/US Letter): 20 ppm. Network ready, Wi-Fi. Product colour: Black, White





Printing		Performance	
Colour * Print technology * Duplex printing * Maximum resolution *	X Laser X 2400 x 600 DPI	Processor family Processor model Processor frequency Sound pressure level (printing)	ARM Cortex ARM9 200 MHz 51 dB
Print speed (black, normal quality, A4/US Letter) *	20 ppm	Design	
Time to first page (black, normal) N-up printing	10 s 2, 4, 6, 9, 16, 25	Product colour * Built-in display *	Black, White X
Features		Power	
Recommended duty cycle Printing colours * Number of print cartridges * Page description languages *	250 - 1800 pages per month Black 1 GDI	Power consumption (printing) * Power consumption (standby) Power consumption (PowerSave) Power consumption (off)	380 W 40 W 0.7 W 0.28 W
Input & output capacity		AC input voltage AC input frequency	220 - 240 V 50/60 Hz
Total number of input trays * Total input capacity * Total output capacity *	1 150 sheets 50 sheets		50,00 112
Paper handling			
Maximum ISO A-series paper size * Paper tray media types * ISO A-series sizes (A0A9) * ISO B-series sizes (B0B9) Non-ISO print media sizes Custom media width Custom media length Paper tray media weight	A4 Plain paper, Recycled paper A4, A5 B5 Executive, Folio, Letter, Legal 148 - 216 mm 148 - 355.6 mm 65 - 105 g/m²		
Ports & interfaces			
Standard interfaces USB 2.0 ports quantity	USB 1.1, USB 2.0, Wireless LAN 1		
Network			
Network ready Wi-Fi * Ethernet LAN * Wi-Fi standards	✓ ✓ ★ 802.11b, 802.11g, Wi-Fi 4 (802.11n)		


Network		System requirements	
Bluetooth	×		Windows 7 Home Basic, Windows 7
Security algorithms Supported network protocols (IPv4)	128-bit WEP, 64-bit WEP, SMTP- AUTH, WPA-AES, WPA-PSK, WPA- TKIP, WPA2-AES, WPA2-PSK, WPS ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMP, Web Services NDP, RA, DNS Resolver, mDNS,	<ul> <li>Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Interprise, Windows 8, I Enterprise, Windows 1, I Enterprise, Windows 1, I Enterprise, Windows 1, I Enterprise, Windows Vista Enterprise, Windows</li></ul>	Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7
Supported network protocols (IPv6)	LLMNR responder, LPR/LPD, Custom Raw Port/ Port 9100, IPP, FTP Server, SNMPv1/v2c, HTTP Server, TFTP Client/Server, SMTP Client, ICMPv6, Web Services		Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows
Mobile printing technologies	Brother iPrint & Scan		Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home
Performance			Basic x64, Windows Vista Home
Internal memory * Built-in processor	32 MB ✔		Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional x64
		Mac operating systems supported	Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
		Linux operating systems supported	1
		Server operating systems supported	Windows Server 2003, Windows Server 2003 x64, Windows Server 2008, Windows Server 2008 R2, Windows Server 2008 x64, Windows Server 2012 R2 x64, Windows Server 2012 x64
		Operational conditions	
		Operating temperature (T-T)	10 - 32 °C
		Storage temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H) Storage relative humidity (H-H)	20 - 80% 35 - 85%
		Weight & dimensions	
		Width	340 mm
		Depth	238 mm
		Height	189 mm
		Weight	4.6 kg
		Packaging data	
		Package width	415 mm
		Package depth	303 mm
		Package height Package weight	324 mm 5.5 kg
		Technical details	
		Harmonized System (HS) code	84433210
		Other features	
		Power LED	√
		Stand-by LED	4



4977766742221



4056572599219



4977766742641

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.