

ZYXEL

Zyxel WAC6502D-S 866 Mbit/s White Power over Ethernet (PoE)

Brand : Zyxel

Product code: WAC6502D-S-EU0101F

Product name : WAC6502D-S



802.11ac Dual Radio Unified Pro Access Point, 2.4/5 GHz, IEEE 802.11 a/b/g/n/ac
Zyxel WAC6502D-S. Maximum data transfer rate: 866 Mbit/s, Ethernet LAN data rates: 10,100,1000 Mbit/s, Frequency band: 2.4 - 5 GHz. Security algorithms: 802.1x RADIUS, WEP, WPA, WPA2, WPA2-PSK. AC input voltage: 100 - 240 V, AC input frequency: 50 - 60 Hz. Product colour: White, Certification: FCC Part 15C, FCC Part 15E, ETSI EN 300 328, EN 301 893, LP0002, EN 60601-1-2 FCC Part 15B, EN....
Antenna features: Integrated antenna, Antenna gain level (max): 6 dBi

Features		Design	
2.4 GHz *	✓	Product colour *	White
5 GHz *	✓	Certification	FCC Part 15C, FCC Part 15E, ETSI EN 300 328, EN 301 893, LP0002, EN 60601-1-2 FCC Part 15B, EN 301 489-1, EN 301 489-17, EN55022, EN55024, EN61000-3-2/-3, BSMI CNS13438 EN 60950-1, IEC 60950-1, BSMI CNS14336-1f
Maximum data transfer rate *	866 Mbit/s	Internal	✗
Ethernet LAN data rates	10,100,1000 Mbit/s	Antenna	
Frequency band	2.4 - 5 GHz	Antenna features	Integrated antenna
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u	Antennas quantity	4
Channel bandwidth	80 MHz	Antenna gain level (max)	6 dBi
MIMO	✓	Weight & dimensions	
MIMO type	Multi User MIMO	Width	236 mm
Modulation	16-QAM, 256-QAM, 64-QAM, BPSK, CCK, DBPSK, DQPSK, QPSK	Depth	227 mm
Maximum Likelihood Detection (MLD)	✓	Height	62 mm
Cyclic Shift Diversity (CSD)	✓	Weight	961 g
Security		Packaging data	
Security algorithms *	802.1x RADIUS, WEP, WPA, WPA2, WPA2-PSK	Package width	308 mm
MAC address filtering	✓	Package depth	323 mm
Number of SSID supported	16	Package height	127 mm
Protocols		Package weight	1.72 kg
DHCP client	✓	Operational conditions	
Ports & interfaces		Operating relative humidity (H-H)	10 - 90%
Ethernet LAN (RJ-45) ports *	2	Operating temperature (T-T)	0 - 50 °C
Power		Storage temperature (T-T)	-40 - 70 °C
Power over Ethernet (PoE) *	✓	Storage relative humidity (H-H)	10 - 90%
AC input voltage	100 - 240 V		
AC input frequency	50 - 60 Hz		



4718937582471



4718937582464

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.