D-Link

D-Link DGS-1210-10 network switch Managed L2 Gigabit Ethernet (10/100/1000) 1U Black, Grey

Brand : D-Link **Product code:** DGS-1210-10

Product name : DGS-1210-10

10-port Gigabit WebSmart Switch with 2 Combo 1000 Base-T/SFP Ports D-Link DGS-1210-10. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. Full duplex. MAC address table: 8000 entries, Switching capacity: 20 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3x. Power connector: DC-in jack. Rack mounting, Form factor: 1U





Management features		Performance	
Switch type * Switch layer Quality of Service (QoS) support Web-based management ARP inspection Configuring Location Settings (CLI) MIB support	Managed L2 ✓ ✓ ✓ ✓	Mean time between failures (MTBF)	205249 h
		Technical details	
		Shipping (inner) case height Shipping (inner) case width Shipping (inner) case length Shipping (inner) case net weight Products per shipping (inner) case	31.7 cm 34.6 cm 38.2 cm 10.4 kg 5 pc(s)
Ports & interfaces		Pallet gross weight (air)	425.5 kg
Basic switching RJ-45 Ethernet ports quantity * Basic switching RJ-45 Ethernet ports type * SFP module slots quantity Power connector	C	Master (outer) cases per pallet (air) Products per pallet (air) Pallet gross length Pallet gross width Pallet height (air)	36 pc(s) 180 pc(s) 110 cm 120 cm 140.3 cm
Network		Pallet gross weight (sea) Master (outer) cases per pallet (sea)	625.9 kg
Network Networking standards * 10G support *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3x ** ** ** ** ** ** ** ** **	Master (outer) cases per pallet (sea) Products per pallet (sea) Pallet height (sea) Shipping (inner) case gross weight	270 pc(s) 2.04 m 11.1 kg
Port mirroring		Power	
Full duplex Flow control support Link aggregation Auto MDI/MDI-X Spanning tree protocol		AC input voltage AC input frequency	100 - 240 V 50/60 Hz
		Power over Ethernet (PoE)	
		Power over Ethernet (PoE) *	×
Head-of-line (HOL) blocking Auto-negotiation	1	Operational conditions	
Data transmission Switching capacity * Forwarding rate	20 Gbit/s 14.88 Mpps	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 40 °C -10 - 70 °C 10 - 95% 5 - 95%
MAC address table * Store-and-forward	8000 entries	Heat dissipation	373.96 BTU/h
Jumbo frames support	√	Weight & dimensions	
Jumbo frames Packet buffer memory	9216 0.512 MB	Width Depth Height	280 mm 126 mm 44 mm
Security		Weight	980 g
Access Control List (ACL)	√	Packaging data	
IGMP snooping MAC address filtering Loop protection	4 4 4	Package width Package depth Package height Package weight	286 mm 325 mm 70 mm 2.08 kg

Multicast features		Logistics data	
Multicast support	✓	Harmonized System (HS) code	85176990
Design			
Rack mounting *	✓		
Stackable *	✓		
Form factor	1U		
Product colour	Black, Grey		









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.