StarTech.com 5 Port Unmanaged Industrial Gigabit Ethernet Switch - DIN Rail / Wall-Mountable

Brand : StarTech.com Product code: IES51000

Product name: 5 Port Unmanaged Industrial Gigabit

Ethernet Switch - DIN Rail / Wall-Mountable


StarTech.com 5 Port Unmanaged Industrial Gigabit Ethernet Switch - DIN Rail / Wall-Mountable Network Switch - Rugged IP30 Gigabit Switch

StarTech.com 5 Port Unmanaged Industrial Gigabit Ethernet Switch - DIN Rail / Wall-Mountable. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 5. Full duplex. Switching capacity: 2 Gbit/s. Networking standards: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3u. Power connector: DC-in jack. Wall mountable





Management features		Power	
Switch type *	Unmanaged	Input voltage	12 - 58 V
Ports & interfaces		Power consumption (typical)	3.63 W
Basic switching RJ-45 Ethernet ports 5		Power over Ethernet (PoE)	
quantity *		Power over Ethernet (PoE) *	×
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Operational conditions	
Power connector	DC-in jack	Operating temperature (T-T)	-40 - 75 °C
Network		Storage temperature (T-T)	-40 - 85 °C
	IEEE 802.1p, IEEE 802.3, IEEE	Operating relative humidity (H-H)	5 - 95%
Networking standards *	802.3ab, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3u	Weight & dimensions	
10G support * Full duplex Link aggregation Auto MDI/MDI-X	X 4 4 4	Width Depth Height Weight	89 mm 111 mm 28 mm 328 g
Data transmission	,	Packaging data	
Switching capacity * Store-and-forward Jumbo frames support	2 Gbit/s ✓	Manual Wall mounting kit Terminal block included Mounting brackets included	* * * * * * * * * *
Design		Screws included	·
Product colour Housing material LED indicators International Protection (IP) code Wall mountable Certification	Black Steel Activity, Link, Power IP30 ✓ CE, FCC, RoHS, REACH	DIN rail included Package width Package depth Package height Package weight	139 mm 176 mm 83 mm 523 g
	CL, I CC, NUITS, NEACH	Logistics data	
Performance Maximum cable length Buffer size	100 m 128 KB	Harmonized System (HS) code	85176990









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.