



# Eaton EMAB05 power distribution unit (PDU) 24 AC outlet(s) 0U Black

Brand : Eaton

Product code: EMAB05

Product name : EMAB05

ePDU G3 Managed, 7kW, 230V In, IEC 60309 (32A, Single-phase) In, 20x C13 Out, 4x C19 Out

[Eaton EMAB05 power distribution unit \(PDU\) 24 AC outlet\(s\) 0U Black:](#)

**Switch and meter outlets & IT equipment across A and B feed: Combines both Switched and Metered Outlet functionality together in 1 ePDU**

ePDU G3 Managed models allow complete lights-out control and metering of devices including devices powered across multiple ePDUs. They include IEC Class 1 ( $\pm 1\%$ ) billing grade accuracy, an advanced hot-swap meter with LCD pixel display showing V, W, A and kWh, and the ability to daisy chain 8 ePDUs to share the same network connection and IP address.

Eaton EMAB05. PDU types: Managed, Rack capacity: 0U, Type: Single-phase. AC outlets quantity: 24 AC outlet(s), AC outlet types: C13 coupler, C19 coupler, Power plug: IEC 60309. Cable length: 3 m.

Management protocols: SNMP, Telnet, Firmware upgradeable via: Network, USB. Nominal input voltage: 230 V, Maximum current: 32 A, AC input frequency: 50 Hz



Design		Power	
PDU types *	Managed	Nominal input voltage *	230 V
Type	Single-phase	AC input frequency	50 Hz
Form factor	Rackmount	Maximum current *	32 A
Rack mounting	✓	Nominal output voltage	230 V
Rack capacity *	0U	Maximum input current per phase	32 A
Mounting	Vertical	Maximum power	7400 W
Product colour	Black	Weight & dimensions	
Cable colour	Black	Width	53 mm
Display	LCD	Depth	1604 mm
Ports & interfaces		Dimensions (WxDxH)	53 x 1604 x 52 mm
AC outlets quantity *	24 AC outlet(s)	Height	52 mm
Power plug	IEC 60309	Weight	4.9 kg
AC outlet types *	C13 coupler, C19 coupler	Packaging data	
Ethernet LAN (RJ-45) ports	1	Package weight	7 kg
Output connections	20 x C13 & 4 x C19	Packaging content	
Features		Cables included	LAN (RJ-45)
LED indicators	✓	Rack mount kit	✓
Cable length	3 m	Operational conditions	
Management features		Operating temperature (T-T)	0 - 60 °C
Management protocols	SNMP, Telnet	Technical details	
Firmware upgradeable	✓	Sustainability certificates	RoHS
Firmware upgradeable via	Network, USB		



3553340697029

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.