FATON

Eaton ESWB05 power distribution unit (PDU) 24 AC outlet(s) 0U Black

Brand : Eaton Product code: ESWB05

Product name: ESWB05

Switched, 7kW, 230V In, IEC 60309 (32A, Single-phase) In, 20x C13 Out, 4x C19 Out

Eaton ESWB05 power distribution unit (PDU) 24 AC outlet(s) 0U Black:

ePDU G3 Switched models allow lights-out control of devices including switching devices powered across multiple ePDUs. They include IEC Class 1 ($\pm 1\%$) billing grade accuracy, an advanced hot-swap meter with LCD pixel display showing V, W, A and kWh, and the ability to daisy chain 8 ePDUs to share the same network connection and IP address.

Eaton ESWB05. PDU types: Switched, Rack capacity: 0U, Type: Single-phase. AC outlets quantity: 24 AC outlet(s), AC outlet types: C13 coupler, C19 coupler, Power plug: IEC 60309. Cable length: 3 m. Management protocols: SNMP, Telnet, Firmware upgradeable via: Network, USB. Nominal input voltage: 230 V, Maximum current: 32 A, AC input frequency: 50 Hz





Design		Power	
PDU types * Type Form factor Rack mounting Rack capacity * Mounting Product colour	Switched Single-phase Irm factor Rackmount Ick mounting Ick capacity * Out Ounting Vertical Oduct colour Switched Switched Out	Nominal input voltage * AC input frequency Maximum current * Nominal output voltage Maximum input current per phase Maximum power Weight & dimensions	230 V 50 Hz 32 A 230 V 32 A 7400 W
Cable colour Display Ports & interfaces	Black LCD	Width Depth Dimensions (WxDxH)	53 mm 1604 mm 53 x 1604 x 52 mm
AC outlets quantity * 24 AC outlet(s) Power plug IEC 60309 AC outlet types * C13 coupler, C19 coupler	IEC 60309	Height Weight	52 mm 4.9 kg
Ethernet LAN (RJ-45) ports Output connections	1 20 x C13 & 4 x C19	Packaging data Package weight	7 kg
Features LED indicators Cable length	√ 3 m	Packaging content Cables included Rack mount kit	LAN (RJ-45) ✓
Management features Management protocols Firmware upgradeable	SNMP, Telnet ✓	Operational conditions Operating temperature (T-T) Technical details	0 - 60 °C
Firmware upgradeable via	Network, USB	Sustainability certificates	RoHS



3553340696022

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.