

Vertiv Avocent MPU2016DAC KVM switch Rack mounting Black

Brand : Vertiv Product family: Avocent

Product code: MPU2016DAC-001



Product name : MPU2016DAC KVM switch Rack mounting Black

MPU2016DAC KVM switch Rack mounting Black

Vertiv Avocent MPU2016DAC KVM switch Rack mounting Black:

The Avocent MergePoint Unity appliance is the fourth generation KVM over IP appliance from Avocent. This appliance provides IT administrators a complete remote management solution to access and control servers, networking equipment and other devices found in data centers and branch offices. The MergePoint Unity switch enhances the in-band management typically done through the NIC of IT equipment by providing secure and remote out-of-band connections directly to the physical KVM, USB and serial ports. This unified approach enables IT administrators a faster method to diagnose, reconfigure or restore equipment to meet SLAs and minimize downtime.

Ports & interfaces		Power	
'	JSB JSB /GA RJ-45, USB A, VGA (D-Sub)	Power source AC input voltage AC input frequency Power consumption (typical) External power adapter	AC 100 - 240 V 50 - 60 Hz 40 W
Console USB ports quantity	4	Operational conditions	
Network Ethernet LAN Ethernet LAN (RJ-45) ports Cabling technology	✓ 2 10/100/1000Base-T(X)	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 50 °C -20 - 70 °C 20 - 80% 5 - 95%
Security algorithms	128-bit SSL, AES, DES, FIPS 140-2	Weight & dimensions	
Performance		Width	437 mm
Maximum resolution * Maximum analog resolution Video bandwidth Number of users	1680 x 1200 pixels 1600 x 1200 pixels 60 Hz 1 user(s)	Depth Height Weight	431.8 mm 340 mm 3.9 kg
	1 0301(3)	Packaging content	
Design Rack mounting *	1U * Black rial Metal ✓	Quick installation guide Rack mount kit	1
Rack capacity Product colour *		Logistics data	
Housing material		Harmonized System (HS) code	85176200
Cascadable		Other features	
LED indicators		Connectivity technology	Wired
Certification		I/O ports	5 x USB 2.0, 2 x RJ45, 1 x VGA, 1 x RS-232
		Dimensions (WxDxH) Ports quantity Power requirements	170 x 133.8 x 17.2 mm 16 100 - 240 VAC









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.