StarTech.com 4-bay mobile rack backplane for 2.5in SATA/SAS drives

Brand : StarTech.com Product code: SATSASBP425

Product name : 4-bay mobile rack backplane for 2.5in SATA/SAS drives

StarTech.com 4-Bay Mobile Rack Backplane for 2.5in SATA/SAS Drives - Hot Swap SSDs/HDDs from 5-15mm - Supports SAS II & SATA III (6 Gbps)


StarTech.com 4-bay mobile rack backplane for 2.5in SATA/SAS drives. Size (imperial): 13.3 cm (5.25"), Type: Storage drive tray, Maximum HDD capacity: 2000 GB. Width: 146 mm, Depth: 152 mm, Height: 42 mm. Package width: 194 mm, Package depth: 216 mm, Package height: 80 mm. Cables included: SATA, Number of lock keys included: 2 pc(s). Sustainability certificates: RoHS







	Weight & dimensions	
al) * 13.3 cm (5.25") Storage drive tray 4 DD capacity 2000 GB 2.5" Ce Serial ATA, Serial ATA II, Serial ATA III, Serial ATA III, Serial Attached SCSI (SAS) Black Aluminium, Steel torage drive heights 5,9.5,12.5,15 mm 20 dB ans 2 fan(s) er 4 cm er rate 6 Gbit/s Activity, Power Sleeve bearing CE, FCC	Width Depth Height Weight	146 mm 152 mm 42 mm 760 g
	Packaging data Package width Package depth Package height Package weight	194 mm 216 mm 80 mm 1.04 kg
	Packaging content Cables included Screws included Number of lock keys included Number of screws	SATA ✓ 2 pc(s) 24
	Operational conditions Storage temperature (T-T) Operating temperature (T-T)	-20 - 55 °C 0 - 55 °C
×	Operating relative humidity (H-H) Sustainability Sustainability certificates Technical details	5 - 65% RoHS
	Storage drive tray 4 2000 GB 2.5" Serial ATA, Serial ATA II, Serial ATA III, Serial Attached SCSI (SAS) Black Aluminium, Steel 5,9.5,12.5,15 mm 1 20 dB 2 fan(s) 4 cm 6 Gbit/s Activity, Power Sleeve bearing CE, FCC	13.3 cm (5.25") Storage drive tray 4 Height 2000 GB 2.5" Serial ATA, Serial ATA II, Serial ATA III, Serial Attached SCSI (SAS) Black Aluminium, Steel 5,9.5,12.5,15 mm ✓ Packaging data Package width Package depth Package height Package weight ✓ Packaging content Cables included Screws included Screws included Number of lock keys included Number of screws Activity, Power ✓ Sleeve bearing CE, FCC Derational conditions Storage temperature (T-T) Operating temperature (T-T) Operating relative humidity (H-H) Sustainability Sustainability certificates





065030859837

0065030859837



5054629784181

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.