## xerox

## Everyday Remanufactured Everyday Yellow Remanufactured Toner by Xerox replaces HP 130A (CF352A), Standard Capacity

Brand : Xerox Product family: Everyday Product code: 006R03244

Remanufactured

Product name: Everyday Yellow Remanufactured Toner by Xerox replaces HP 130A (CF352A), Standard Capacity



Everyday Yellow Remanufactured Toner by Xerox replaces HP 130A (CF352A), Standard Capacity

Everyday Remanufactured Everyday Yellow Remanufactured Toner by Xerox replaces HP 130A (CF352A), Standard Capacity:

Being environmentally responsible is simply the best way to do business, because it positively impacts the health of our planet, your company and your people. Everyday Remanufactured Toner by Xerox has the lowest carbon footprint than any single-use toner cartridge. Because you shouldn't have to choose between doing your part to reduce your eco-impact and your toner costs. And compatibility with the most popular printer brands means you can enjoy benchmark Xerox quality and stewardship no matter what kind of printer you have.

Everyday Remanufactured Everyday Yellow Remanufactured Toner by replaces HP 130A (CF352A), Standard Capacity. Colour toner page yield: 1000 pages, Printing colours: Yellow, Quantity per pack: 1 pc(s)

Features		Operational conditions	
Compatibility *	Color Laserjet Pro MFP M176, M176n, M177fw	Operating relative humidity (H-H) Storage temperature (T-T)	30 - 70% 0 - 35 °C
Quantity per pack *	1 pc(s)	Storage relative humidity (H-H)	35 - 85%
Cartridge capacity Colour toner page yield	Standard Yield 1000 pages	Weight & dimensions	
Type *	Compatible	Weight	287 g
Printing colours *	Yellow	Package width	352 mm
Brand compatibility *	НР	Package depth	122 mm
Supply type *	Single pack	Package height	165 mm
Replacement for	HP 130A	Package weight	520 g
OEM code	CF352A	Package type	Box
Country of origin	Romania	Logistics data	
Certification	Nordic Swan/ISO14001/RoHs/Reach STMC - ISO9001/ISO19752	Harmonized System (HS) code Products per master (outer) case	8443.99.1000 6 pc(s)
Operational conditions		Troducts per muster (outer) case	5 pc(3)
Operating temperature (T-T)	17 - 25 °C		





095205870336

0095205870336

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.