

## StarTech.com 4-Port HDMI Automatic Video Switch - 4K with Fast Switching

**Brand :** StarTech.com

**Product code:** VS421HD4KA

**Product name :** 4-Port HDMI Automatic Video Switch - 4K with Fast Switching



StarTech.com 4-Port HDMI Automatic Video Switch - 4K 2x1 HDMI Switch with Fast Switching, Auto-sensing and Serial Control

StarTech.com 4-Port HDMI Automatic Video Switch - 4K with Fast Switching. Video port type: HDMI. Product colour: Black, Maximum refresh rate: 30 Hz, Supported graphics resolutions: 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 2560 x 1600 (WQXGA). AC adapter input voltage: 100 - 240 V, AC adapter output voltage: 12 V, AC adapter output current: 1.5 A. Certification: CE, FCC, TAA, REACH. Width: 65 mm, Depth: 156 mm, Height: 20 mm



<b>Ports &amp; interfaces</b>		<b>Weight &amp; dimensions</b>	
Video port type *	HDMI	Height	20 mm
HDMI ports quantity	4	Weight	291 g
HDMI version	1.4	<b>Packaging data</b>	
DC-in jack	✓	Package width	235 mm
<b>Features</b>		Package depth	155 mm
Product colour	Black	Package height	64 mm
HDCP	✓	Package weight	836 g
Maximum refresh rate	30 Hz	<b>Packaging content</b>	
Supported graphics resolutions	1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 2560 x 1600 (WQXGA)	Mounting kit	✓
Supported video modes	1080p	Quick start guide	✓
LED indicators	Activity, Power	Remote control included	✓
Maximum resolution	3840 x 2160 pixels	Cables included	Phone (RJ-11)
Remote control type	IR	AC adapter included	✓
Audio output channels	7.1 channels	Mounting brackets included	✓
<b>Power</b>		<b>Operational conditions</b>	
AC adapter input voltage	100 - 240 V	Operating temperature (T-T)	0 - 40 °C
AC adapter output voltage	12 V	Storage temperature (T-T)	-10 - 60 °C
AC adapter output current	1.5 A	Operating relative humidity (H-H)	0 - 80%
Power consumption (typical)	18 W	<b>Sustainability</b>	
<b>Certificates</b>		Sustainability certificates	RoHS
Certification	CE, FCC, TAA, REACH	<b>Technical details</b>	
<b>Weight &amp; dimensions</b>		Audio support	✓
Width	65 mm	<b>Logistics data</b>	
Depth	156 mm	Harmonized System (HS) code	85176990



0065030862370



065030862370

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-APR-2023. Prints or copies of Information are only valid on the printed Publication date