brother
at your side

Brother PDS-6000F scanner Flatbed & ADF scanner 600 x 600 DPI A4 Black

Brand : Brother   **Product code:** PDS-6000F

Product name : PDS-6000F

Professional scanner - 60 ppm - duplex - SuperSpeed USB 3.0
Brother PDS-6000F. Maximum scan size: 216 x 5994 mm, Optical scanning resolution: 600 x 600 DPI,
Input colour depth: 48 bit. Scanner type: Flatbed & ADF scanner, Product colour: Black, Display: LCD.
Sensor type: CCD, Light source: LED, Scan file formats: BMP, DOC, HTM, JPG, PDF, PNG, RTF, TIFF, TXT,
XLS, XPS. Auto document feeder (ADF) input capacity: 100 sheets. Maximum ISO A-series paper size: A4,
Scanning media types supported: Labels, Plastic Card, Thin paper, Auto Document Feeder (ADF) media
weight: 28 - 400 g/m²

Scanning

Maximum scan size *	216 x 5994 mm
Optical scanning resolution *	600 x 600 DPI
Colour scanning	✔
Duplex scanning *	✔
Input colour depth	48 bit
Output colour depth	24 bit
Greyscale levels	256
ADF scan speed (b/w, A4)	80 ppm
ADF scan speed (colour, A4)	80 ppm
Black/white scanning colour modes	Monochrome

Design

Scanner type *	Flatbed & ADF scanner
Product colour *	Black
Display	LCD
Built-in display *	✔

Performance

Sensor type *	CCD
Light source	LED
Scan file formats	BMP, DOC, HTM, JPG, PDF, PNG, RTF, TIFF, TXT, XLS, XPS
Scan to	E-mail, FTP, File
Scan drivers	ICA, SANE, TWAIN, WIA
Scanning noise level	55 dB
Internal memory	512 MB
Built-in processor	Avision Vision Max II
Processor frequency	240 MHz

Input capacity

Auto document feeder (ADF) input capacity	100 sheets

Paper handling

Scanning media types supported	Labels, Plastic Card, Thin paper
Maximum ISO A-series paper size *	A4
Auto Document Feeder (ADF) media weight	28 - 400 g/m²

Ports & interfaces

USB port *	✔
USB version	3.2 Gen 1 (3.1 Gen 1)
Standard interfaces	USB 3.2 Gen 1 (3.1 Gen 1)

Power

Power supply type *	AC
Power consumption (typical)	53 W
Power consumption (standby)	17.6 W
Power consumption (off)	0.3 W
Power consumption (PowerSave)	2.7 W

Packaging data

Package width	730 mm
Package depth	439 mm
Package height	386 mm
Package weight	12.3 kg

System requirements

Windows operating systems supported	Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Linux operating systems supported	Debian 5.0, Debian 5.0.1, Debian 5.0.2, Debian 5.0.3, Debian 6.0, Debian 7.0, Debian 8.0, Fedora 10, Fedora 11, Fedora 12, Fedora 13, Fedora 14, Fedora 15, Fedora 18, Fedora 6, Fedora 7, Fedora 8, Fedora 9, SuSE Linux 10, SuSE Linux 10.2, SuSE Linux 10.3, SuSE Linux 11, SuSE Linux 11.1, SuSE Linux 11.2, SuSE Linux 9.3

Operational conditions

Operating temperature (T-T)	5 - 35 °C
Operating relative humidity (H-H)	20 - 80%

Weight & dimensions

Width	323 mm
Depth	613 mm
Height	263 mm
Weight	8.87 kg

Packaging content

Drivers included	✔

Technical details

Sustainability certificates	ENERGY STAR
Harmonized System (HS) code	84716070

4977766754804