NETGEAR M4300-8X8F Managed L3 10G Ethernet (100/1000/10000) 1U Black

Brand: NETGEAR Product code: XSM4316S-100NES

320 Gbps, 10/100/1000/10000, 1U, L3

Product name: M4300-8X8F

NETGEAR M4300-8X8F. Switch type: Managed, Switch layer: L3. Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000), Basic switching RJ-45 Ethernet ports quantity: 8, USB 2.0 ports quantity: 1, Console port: RJ-45/Mini-USB. MAC address table: 16000 entries, Switching capacity: 320 Gbit/s. Networking standards: IEEE 802.11ad, IEEE 802.11az, IEEE 802.3ad, IEEE 802.3az. Rack mounting, Form factor: 1U





Management features		Multicast features	
Switch type *	Managed	Number of multicast groups filtered	4000
Switch layer	L3	Design	
Quality of Service (QoS) support	√	Rack mounting *	√
Web-based management	√	Stackable *	✓
ARP inspection	V	Form factor	10
Ports & interfaces		Product colour	Black
Basic switching RJ-45 Ethernet ports	8	LED indicators	Activity, Power, Speed
quantity * Basic switching RJ-45 Ethernet ports	10G Ethernet (100/1000/10000)	Safety	CSA 22.2 #950, UL 1950)/cUL IEC 950/EN 60950
type * SFP+ module slots quantity	8	Electromagnetic compatibility	CE, FCC 15 A, VCCI A, A EN 55022, (CISPR 22) A, EN 50082-1, EN 55024
Fiber optic connector	SFP+	Performance	
Console port	RJ-45/Mini-USB	Built-in processor	✓
USB 2.0 ports quantity	1	Processor frequency	800 MHz
Network		Internal memory	1024 MB
Networking standards *	IEEE 802.11ad, IEEE 802.11az, IEEE 802.3ad, IEEE 802.3az	Flash memory Noise level	256 MB 36.9 dB
10G support *	✓	Mean time between failures (MTBF)	196120 h
Cable types supported	Cat5, Cat5e, Cat6, Cat7	Power	
Port mirroring	✓		✓
IP routing	✓	Power supply included * Number of power supply units	1
Flow control support	√	AC input voltage	120 - 230 V
Link aggregation	V	Power consumption (max)	49 W
Rate limiting	4		
Auto MDI/MDI-X Spanning tree protocol	4	Power over Ethernet (PoE)	
Auto-sensing	1	Power over Ethernet (PoE) *	×
Auto-negotiation	1	Operational conditions	
VLAN support	V	Operating temperature (T-T)	0 - 50 °C
Virtual LAN features	Private VLAN	Storage temperature (T-T)	-20 - 70 °C
Optical fiber		Operating relative humidity (H-H)	0 - 90%
option liber	10GBASE-LR, 10GBASE-LRM,	Storage relative humidity (H-H)	0 - 95%
Fiber ethernet cabling technology	10GBASE-LR, 10GBASE-LRM, 10GBASE-SR	Operating altitude	0 - 3000 m
Data transmission		Non-operating altitude	0 - 3000 m
Switching capacity *	320 Gbit/s	Heat dissipation	18577 BTU/h
Forwarding rate	357 Mpps	Weight & dimensions	
MAC address table *	16000 entries	Width	212 mm
Store-and-forward	✓	Depth	345 mm
Number of static routes	64	Height	44 mm
	•	Weight	3.32 kg

Data transmission		Packaging data	
Jumbo frames support Jumbo frames	√ 9000	Cables included User guide	AC, LAN (RJ-45), Mini-USB ✓
Security		Rack mount kit Rubber feet	1
DHCP features Access Control List (ACL)	DHCP server, DHCP client ✓ HTTPS, SNMP, SSH	Resource CD	v
Security algorithms		Logistics data	
SSH/SSL support BPDU filtering/protection	√	Harmonized System (HS) code	85176990
Multicast features			
Multicast support	✓		





606449110005

0606449110005

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.