


# StarTech.com HPE J4858C Compatible SFP Module - 1000BASE-SX - 1GbE Multi Mode Fiber Optic Transceiver - 1GE Gigabit Ethernet SFP - LC 550m - 850nm - DDM HPE 1400, 1700, 1820

**Brand :** StarTech.com

**Product code:** J4858CST

**Product name :** HPE J4858C Compatible SFP Module - 1000BASE-SX - 1GbE Multi Mode Fiber Optic Transceiver - 1GE Gigabit Ethernet SFP - LC 550m - 850nm - DDM HPE 1400, 1700, 1820



- 100% HPE J4858C COMPATIBLE: Works with HPE switches like 1400, 1700, 1820, 2520, 2530 and others
  - TECHNICAL SPECS: 1000BASE-SX / 1Gbps / Multi Mode (MMF) / LC Connector / 850nm / Digital Diagnostic Monitoring (DDM) / Distances up to 550m (1804ft)
  - TESTED FOR OEM HOST COMPATIBILITY: Hot-swappable in HPE routers and switches; DDM support reports the transceiver's status to most SNMP network management tools
  - THE IT PRO'S CHOICE: Designed and built for IT Professionals, this SFP module is backed for life (lifetime of module, not network switch), including free lifetime 24/5 multi-lingual technical assistance
  - WORKS WITH MSA COMPLIANT SWITCHES: Also works with switch models from Ubiquiti, D-Link, Netgear, Supermicro, TP-Link and more that accept uncodded modules
- StarTech.com HPE J4858C Compatible SFP Module - 1000BASE-SX - 1GbE Multi Mode (MMF) Fiber Optic Transceiver - 1GE Gigabit Ethernet SFP - LC 550m - 850nm - DDM HPE 1400, 1700, 1820 (J4858CST)



Performance		Operational conditions	
SFP transceiver type *	Fiber optic	Operating temperature (T-T)	0 - 70 °C
Maximum data transfer rate *	1250 Mbit/s	Storage temperature (T-T)	-40 - 85 °C
Interface type *	SFP	Operating relative humidity (H-H)	30 - 75%
Multi-mode fiber (MMF) supported	✓	Weight & dimensions	
Fiber optic connector	LC	Width	14 mm
SFP transceiver standard	SX	Depth	57 mm
Maximum transfer distance	550 m	Height	13 mm
Wavelength	850 nm	Weight	18 g
Networking standards	IEEE 802.3z	Packaging data	
Duplex system	Full, Half	Number of products included	1 pc(s)
Digital Diagnostics Monitoring (DDM)	✓	Package width	119 mm
Wavelength-division multiplexing (WDM)	✗	Package depth	93 mm
Features		Package height	33 mm
Product colour	Silver	Package weight	46 g
Housing material	Aluminium	Technical details	
Hot-swap	✓	Sustainability certificates	RoHS
Mean time between failures (MTBF)	3381761 h	Logistics data	
Certification	CE, FCC, UL	Master (outer) case width	254 mm
Power		Master (outer) case length	305 mm
Power consumption (typical)	1 W	Harmonized System (HS) code	85369010
		Master (outer) case height	200 mm
		Products per master (outer) case	36 pc(s)



0065030865289



065030865289

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.