

StarTech.com HPE J8177C Compatible SFP Module - 1000BASE-T - SFP to RJ45 Cat6/Cat5e - 1GE Gigabit Ethernet SFP - RJ-45 100m - HPE 1810, 1820, 2530

Brand : StarTech.com

Product code: J8177CST

Product name : HPE J8177C Compatible SFP Module - 1000BASE-T - SFP to RJ45 Cat6/Cat5e - 1GE Gigabit Ethernet SFP - RJ-45 100m - HPE 1810, 1820, 2530



- 100% HPE J8177C COMPATIBLE: Works with HPE switches like 1810, 1820, 2530, 2610, 2620 and others
 - TECHNICAL SPECS: 1000BASE-T / 1Gbps / Copper / RJ-45 Connector / Distances up to 100m (328ft)
 - TESTED FOR OEM HOST COMPATIBILITY: Hot-swappable in HPE routers and switches
 - THE IT PRO'S CHOICE: Designed and built for IT Professionals, this SFP module is backed for life (lifetime of module, not network switch), including free lifetime technical assistance
 - WORKS WITH MSA COMPLIANT SWITCHES: Also works with switch models from Ubiquiti, D-Link, Netgear, Supermicro, TP-Link and more that accept uncoded modules
- StarTech.com HPE J8177C Compatible SFP Module - 1000BASE-T - SFP to RJ45 Cat6/Cat5e - 1GE Gigabit Ethernet SFP - RJ-45 100m - HPE 1810, 1820, 2530 (J8177CST)



Performance		Operational conditions	
SFP transceiver type *	Copper	Storage temperature (T-T)	-40 - 85 °C
Maximum data transfer rate *	1000 Mbit/s	Operating relative humidity (H-H)	30 - 75%
Interface type *	SFP	Weight & dimensions	
Fiber optic connector	MiniGBIC	Width	14 mm
Maximum transfer distance	100 m	Depth	68 mm
Networking standards	IEEE 802.3ab	Height	14 mm
Auto MDI/MDI-X	✓	Weight	25 g
Auto-negotiation	✓	Packaging data	
Digital Diagnostics Monitoring (DDM)	✗	Number of products included	1 pc(s)
Ethernet LAN (RJ-45) ports	1	Package width	118 mm
Features		Package depth	92 mm
Product colour	Silver	Package height	34 mm
Housing material	Aluminium	Package weight	53 g
Hot-swap	✓	Technical details	
Mean time between failures (MTBF)	4655371 h	Sustainability certificates	RoHS
Certification	CE, FCC	Logistics data	
Power		Master (outer) case width	355 mm
Power consumption (typical)	1.3 W	Master (outer) case length	410 mm
Operational conditions		Harmonized System (HS) code	85369010
Operating temperature (T-T)	0 - 70 °C	Master (outer) case height	340 mm
		Products per master (outer) case	100 pc(s)



0065030865234



065030865234

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.