

Epson TM-T88VI (551A0) 180 x 180 DPI Wired & Wireless Thermal POS printer

Brand : Epson

Product code: C31CE94551A0

Product name : TM-T88VI (551A0)

- Fast print speeds: Print at speeds of up to 350mm/s
- Proven reliability: Epson's proven track record for reliability
- Co-existence: Allows PC, mobile and web connection at the same time
- Server direct print: Print directly from web server to any connected receipt printer
- Beacon support: Lets mobile devices print to the nearest available printer

Thermal Line, 350mm/sec, 180 x 180DPI, USB, Ethernet, Bluetooth, Black

Epson TM-T88VI (551A0). Print technology: Thermal, Type: POS printer, Maximum resolution: 180 x 180 DPI. Maximum roll diameter: 8.3 cm. Connectivity technology: Wired & Wireless, USB connector: USB Type-A / USB Type-B, Standard interfaces: Bluetooth, Ethernet, NFC, USB 2.0. Mean time between failures (MTBF): 360000 h, Autocutter durability: 3 million cuts, Country of origin: China. Product colour: Black



Printing		Weight & dimensions	
Maximum resolution	180 x 180 DPI	Height	148 mm
Print speed	350 mm/sec	Weight	1.6 kg
Print technology *	Thermal	Packaging data	
Type *	POS printer	Quantity per pack	1 pc(s)
Paper handling		Package width	196 mm
Maximum roll diameter	8.3 cm	Package depth	240 mm
Ports & interfaces		Package height	235 mm
USB port *	✓	Package weight	2.66 kg
USB connector	USB Type-A / USB Type-B	Logistics data	
Bluetooth	✓	Harmonized System (HS) code	84433210
Connectivity technology *	Wired & Wireless	Products per master (outer) case	4 pc(s)
Near Field Communication (NFC)	✓	Master (outer) case width	400 mm
Standard interfaces	Bluetooth, Ethernet, NFC, USB 2.0	Master (outer) case length	490 mm
Network		Master (outer) case height	255 mm
Ethernet LAN *	✓	Products per pallet	128 pc(s)
Features		Products per pallet layer	16 pc(s)
Mean time between failures (MTBF)	360000 h	Pallet gross width	80 cm
Cutter	✓	Pallet gross length	120 cm
Autocutter durability	3 million cuts	Pallet gross height	2.03 m
Country of origin	China	Products per pallet (UK)	192 pc(s)
Safety	UL, CSA	Products per pallet layer (UK)	24 pc(s)
Design		Pallet width (UK)	100 cm
Product colour *	Black	Pallet length (UK)	120 cm
		Pallet height (UK)	2.03 m
Operational conditions		Technical details	
Operating temperature (T-T)	5 - 45 °C	Sustainability certificates	ENERGY STAR
Storage temperature (T-T)	-10 - 50 °C	Other features	
Operating relative humidity (H-H)	10 - 90%	Buffer size	4 KB
Weight & dimensions		Electromagnetic compatibility	CE, EN55024
Width	145 mm	Mean cycles between failures (MCBF)	70000000
Depth	195 mm		



8715946623726

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-APR-2023. Prints or copies of Information are only valid on the printed Publication date