Epson TM-T88VI (112) 180 x 180 DPI Wired Direct thermal POS printer

Brand : Epson

Product name : TM-T88VI (112)

Product code: C31CE94112

Thermal line, 350mm/sec, 180 x 180DPI, receipt, USB 2.0 Type A, USB 2.0 Type B, RS-232, Ethernet
Epson TM-T88VI (112). Print technology: Direct thermal, Type: POS printer, Maximum resolution: 180 x
180 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 80 mm, Media thickness: 48 - 80 mm.
Connectivity technology: Wired, USB connector: USB Type-A / USB Type-B, Serial interface type: RS-232.
Mean time between failures (MTBF): 360000 h, Autocutter durability: 3 million cuts, Print head life: 200
km. Product colour: Black

Printing

Maximum resolution	180 x 180 DPI
Print speed	300 mm/sec
Print speed (receipt)	350 mm/sec
Printing characters	Text, Graphic, Barcode
Character sets	ANK
Print technology *	Direct thermal
Type *	POS printer

Paper handling

Maximum roll diameter	8.3 cm
Supported paper width	80 mm
Media thickness	48 - 80 mm

Ports & interfaces

USB port *	✓
USB connector	USB Type-A / USB Type-B
Serial interface *	✓
Serial interface type	RS-232
Connectivity technology *	Wired
Near Field Communication (NFC)	✓
Optional connectivity	Wireless LAN
Standard interfaces	Ethernet, RS-232, USB 2.0

Network

Ethernet LAN *	✓

Features

Mean time between failures (MTBF)	360000 h
Cutter	✓
Half-cutter	✓
Autocutter durability	3 million cuts
Print head life	200 km
Country of origin	China
Mounting position	Horizontal
Wall mountable	✓

Operational conditions

Storage temperature (T-T)	-10 - 50 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	145 mm
Depth	195 mm
Height	148 mm
Weight	1.6 kg

Packaging data

Quantity per pack	1 pc(s)
Package width	193 mm
Package depth	240 mm
Package height	235 mm
Package weight	2.62 kg

Print technology

Column capacity	58/80

Logistics data

Harmonized System (HS) code	84433210
Products per master (outer) case	4 pc(s)
Master (outer) case width	400 mm
Master (outer) case length	490 mm
Master (outer) case height	255 mm
Products per pallet	128 pc(s)
Products per pallet layer	16 pc(s)
Pallet gross width	80 cm
Pallet gross length	120 cm
Pallet gross height	15 cm
Products per pallet (UK)	192 pc(s)
Products per pallet layer (UK)	24 pc(s)
Pallet width (UK)	100 cm
Pallet length (UK)	120 cm

Features

Built-in sensors details	Paper Near End Sensor, Cover Open Sensor, Papier-Sensor
Safety	UL, CSA
Certification	CE, EN55024

Design

Product colour *	Black

Power

Power source type *	AC
AC input voltage	24 V
Power plug type	Type C
Power supply type	AC

Operational conditions

Operating temperature (T-T)	5 - 45 °C

Logistics data

Pallet height (UK)	15 cm

Technical details

Changeable interface	✔
Lifetime	20000000 lines

Other features

Buffer size	4 KB
Electromagnetic compatibility	CE marking, EN55024
Mean cycles between failures (MCBF)	70000000
Print head life	200.000.000 Impulse

8715946622026

2530091610058