



APC Smart-UPS 3000VA Line-Interactive 3 kVA 2700 W 9 AC outlet(s)

Brand : APC

Product code: SMT3000RM12UNC

Product name : Smart-UPS 3000VA



230 V, 2.7 KW / 3 kVA, 50/60 Hz, RJ-45, SmartSlot, USB, 480 x 683 x 86 mm, 44.19 kg
APC Smart-UPS 3000VA. UPS topology: Line-Interactive, Output power capacity: 3 kVA, Output power: 2700 W. AC outlet types: C13 coupler, C19 coupler, C20 coupler, Power plug: C20 coupler, AC outlets quantity: 9 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 547 Ah, Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 480 mm, Depth: 683 mm, Height: 86 mm




| Features | | Design | |
|---------------------------------|---------------------------------------|-----------------------------------|--|
| UPS topology * | Line-Interactive | Form factor * | Rackmount |
| Output power capacity * | 3 kVA | Rack capacity | 2U |
| Output power * | 2700 W | Cable length | 2 m |
| Waveform * | Sine | Product colour * | Black |
| Input operation voltage (min) * | 151 V | Display type | LCD |
| Input operation voltage (max) * | 302 V | LED indicators | ✓ |
| Input frequency * | 50/60 Hz | Certification | CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE |
| Output operation voltage (min) | 220 V | Operational conditions | |
| Output operation voltage (max) | 240 V | Operating temperature (T-T) | 0 - 40 °C |
| Output frequency | 50/60 Hz | Storage temperature (T-T) | -15 - 45 °C |
| Surge energy rating | 320 J | Operating relative humidity (H-H) | 0 - 95% |
| Response time | 4 ms | Storage relative humidity (H-H) | 0 - 95% |
| Emergency Power Off (EPO) | 0 | Operating altitude | 0 - 3000 m |
| Noise level | 55 dB | Non-operating altitude | 0 - 15000 m |
| Surge protection | ✓ | Technical details | |
| Audible alarm(s) | ✓ | Sustainability certificates | RoHS |
| Web-based management | ✓ | Harmonized System (HS) code | 85078000 |
| Audible alarm modes | Battery replacement | Weight & dimensions | |
| Auto-restart | ✓ | Width | 480 mm |
| Ports & interfaces | | Depth | 683 mm |
| AC outlet types | C13 coupler, C19 coupler, C20 coupler | Height | 86 mm |
| Power plug | C20 coupler | Weight | 44.2 kg |
| AC outlets quantity | 9 AC outlet(s) | Package width | 600 mm |
| USB 2.0 ports quantity | 1 | Package depth | 980 mm |
| Ethernet LAN (RJ-45) ports | 1 | Package height | 254 mm |
| Battery | | Package weight | 51.6 kg |
| Battery technology | Sealed Lead Acid (VRLA) | Packaging data | |
| Battery capacity | 547 Ah | Rack mount kit | ✓ |
| Battery recharge time | 3 h | Cables included | Input power cable, USB cable |
| Hot-swap battery | ✓ | Quick installation guide | ✓ |
| Automatic battery test | ✓ | Resource CD | ✓ |
| Cold start | ✓ | Logistics data | |
| | | Products per pallet | 8 pc(s) |

Other features

Output voltage 230 V



0731304327707



731304327707

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.