



## APC SRT2200RMXLI-NC uninterruptible power supply (UPS) Double-conversion (Online) 2.2 kVA 1980 W 12 AC outlet(s)



Brand : APC

Product code: SRT2200RMXLI-NC

Product name : SRT2200RMXLI-NC


APC Smart-UPS SRT 2200VA RM 230V Network Card

APC SRT2200RMXLI-NC. UPS topology: Double-conversion (Online), Output power capacity: 2.2 kVA, Output power: 1980 W. AC outlet types: C13 coupler, C19 coupler, AC outlets quantity: 12 AC outlet(s), Serial interface type: RJ-45. Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 367 VAh, Battery life (max): 5 year(s). Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 432 mm, Depth: 584 mm, Height: 85 mm

Features		Battery	
UPS topology *	Double-conversion (Online)	Battery recharge time	3 h
Output power capacity *	2.2 kVA	<b>Design</b>	
Output power *	1980 W	Form factor *	Rackmount
Waveform *	Sine	Rack capacity	2U
Input operation voltage (min) *	160 V	Cable length	2.44 m
Input operation voltage (max) *	275 V	Product colour *	Black
Input frequency *	40 - 70 Hz	Display type	LCD
Output operation voltage (min)	220 V	LED indicators	✓
Output operation voltage (max)	240 V	International Protection (IP) code	IP20
Surge energy rating	340 J	Certification	CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE
Crest factor	3:1	<b>Operational conditions</b>	
Emergency Power Off (EPO)	✓	Operating temperature (T-T)	0 - 40 °C
Output voltage Total Harmonic Distortion (THD)	2%	Storage temperature (T-T)	-20 - 50 °C
Noise level	55 dB	Operating relative humidity (H-H)	0 - 95%
Audible alarm(s)	✓	Storage relative humidity (H-H)	0 - 95%
<b>Ports &amp; interfaces</b>		Operating altitude	0 - 3000 m
AC outlet types	C13 coupler, C19 coupler	Non-operating altitude	0 - 15000 m
AC outlets quantity	12 AC outlet(s)	<b>Technical details</b>	
Number of output IEC jumpers	2	Sustainability certificates	RoHS, ENERGY STAR
USB port	✓	Harmonized System (HS) code	85078000
Serial interface	✓	<b>Weight &amp; dimensions</b>	
Serial interface type	RJ-45	Width	432 mm
Ethernet LAN (RJ-45) ports	1	Depth	584 mm
SmartSlot	✓	Height	85 mm
<b>Battery</b>		Weight	25 kg
Battery technology	Sealed Lead Acid (VRLA)	Package width	599 mm
Battery capacity	367 VAh	Package depth	810 mm
Number of batteries supported	1	Package height	246 mm
Battery life (max)	5 year(s)	Package weight	34 kg
		<b>Other features</b>	
		Output voltage	230 V



0731304327561



731304327561

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.