



## Lindy USB 3.1 Hub & Gigabit Ethernet Adapter

**Brand :** Lindy

**Product code:** 43176

**Product name :** USB 3.1 Hub & Gigabit Ethernet Adapter

- Connects a USB 3.0 Type A computer to a Gigabit Ethernet network
- Provides three USB 3.1 Gen 1 / 3.0 Type A ports
- Supports 10/100/1000BASE-T, full and half duplex mode
- USB 3.1 Gen 1 / 3.0 SuperSpeed data transfer rates up to 5Gbps

USB 3.0 Hub & Gigabit Ethernet Converter

Lindy USB 3.1 Hub & Gigabit Ethernet Adapter. Host interface: USB 3.2 Gen 1 (3.1 Gen 1) Type-A, Hub interfaces: RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A. Data transfer rate: 5000 Mbit/s, Product colour: Black, Housing material: Plastic. Ethernet interface type: Gigabit Ethernet, Ethernet LAN data rates: 10,100,1000 Mbit/s, Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u. Power supply type: USB. Width: 40 mm, Depth: 110 mm, Height: 20 mm



Ports & interfaces		Weight & dimensions	
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-A	Width	40 mm
Hub interfaces *	RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A	Depth	110 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3	Height	20 mm
Ports quantity *	4	Weight	60 g
Ethernet LAN (RJ-45) ports	1	<b>Packaging data</b>	
<b>Features</b>		Quantity per pack	1 pc(s)
Data transfer rate *	5000 Mbit/s	Package width	175 mm
Product colour	Black	Package depth	129 mm
Housing material	Plastic	Package height	30 mm
Cable length	0.29 m	Package weight	100 g
Certification	CE, UKCA, FCC, RoHS, REACH	Package type	Blister
<b>Network</b>		<b>Packaging content</b>	
Ethernet interface type	Gigabit Ethernet	Manual	✓
Ethernet LAN data rates	10,100,1000 Mbit/s	<b>Operational conditions</b>	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u	Maximum operating temperature	70 °C
<b>Power</b>		Operating temperature (T-T)	0 - 70 °C
Power supply type	USB	Operating temperature (T-T)	0 - 158 °F
<b>System requirements</b>		Storage temperature (T-T)	-10 - 55 °C
Windows operating systems supported	✓	Operating relative humidity (H-H)	10 - 90%
Mac operating systems supported	✓	Storage relative humidity (H-H)	10 - 90%
Linux operating systems supported	✓	<b>Performance</b>	
		Harmonized System (HS) code	84719000
		<b>Other features</b>	
		Chipset	AX88179 (LAN), VL813 (Hub)



4002888431767

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.