



## V7 UPS 750VA Desktop UK

**Brand :** V7

**Product code:** UPS1DT750-1K

**Product name :** UPS 750VA Desktop UK

450W, 750VA, 632 Joules, 1.83 m, USB, RJ-11, RJ-45, 3.4 kg, UK

[V7 UPS 750VA Desktop UK:](#)

This UPS provide a backup power source for desktop computers, network workstations and other professional and consumer electronic devices. It ensures a consistent flow of electricity to help prevent equipment failure and data loss during power failures, brownouts, or other power issues that can occur with power in your building. The USB port allows built in UPS configuration and control, and auto-shutdown features for your computers or servers.


- 750vA Desktop UPS with 6 Outlets (3 battery backup + 3 surge only)
- Convenient and compact desktop design with touch screen LCD to display UPS information
- Energy Star Certified ensuring efficient and eco friendly power.
- USB connectivity to your PC for optional advanced monitoring and control
- Audio & Visual alarms for immediate warning of battery, load, and other issues



Features		Design	
Output power capacity *	0.75 kVA	Cable length	1.83 m
Output power *	450 W	Product colour *	Black
Waveform *	Sine	Display type	LCD
Surge energy rating	632 J	Certification	FCC, TUV, REACH
Hold time (min)	6 ms	<b>Operational conditions</b>	
Hold time (max)	10 ms	Operating temperature (T-T)	0 - 40 °C
Noise level	40 dB	Operating relative humidity (H-H)	0 - 90%
Surge protection	✓	<b>Technical details</b>	
Audible alarm(s)	✓	Sustainability certificates	RoHS, ENERGY STAR
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm	<b>Weight &amp; dimensions</b>	
<b>Ports &amp; interfaces</b>		Width	158.5 mm
AC outlets quantity	6 AC outlet(s)	Depth	305 mm
USB port	✓	Height	95 mm
Modem (RJ-11) ports	1	Weight	3.4 kg
Ethernet LAN (RJ-45) ports	1	Package width	142 mm
<b>Battery</b>		Package depth	376 mm
Battery technology	Sealed Lead Acid (VRLA)	Package height	237 mm
Battery capacity	5 Ah	Package weight	3.7 kg
Battery voltage	12 V	<b>Packaging data</b>	
Typical backup time at half load	5.5 min	Quick installation guide	✓
Battery recharge time	6 h	Warranty card	✓
<b>Design</b>		<b>Logistics data</b>	
Form factor *	Compact	Harmonized System (HS) code	85078000



0662919091403



662919091403

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.