

Epson TM-T70II (022A1) 180 x 180 DPI Wired Direct thermal POS printer

Brand : Epson

Product code: C31CD38022A1

Product name : TM-T70II (022A1)



Thermal Line, 250mm/sec, 180 x 180DPI, USB 2.0 Type B, Ethernet
Epson TM-T70II (022A1). Print technology: Direct thermal, Type: POS printer, Maximum resolution: 180 x 180 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 80 mm. Connectivity technology: Wired, USB connector: USB Type-B, Standard interfaces: Ethernet, USB 2.0. Sound pressure level (printing): 55 dB, Mean time between failures (MTBF): 360000 h, Autocutter durability: 1.7 million cuts. Product colour: Grey

Printing		Power	
Colour	✗	Power plug type	Type C
Maximum resolution	180 x 180 DPI	Power supply type	AC
Print speed	250 mm/sec	Power consumption	100 mA
Print speed (receipt)	250 mm/sec	Operational conditions	
Character sets	ANK	Operating temperature (T-T)	5 - 45 °C
Print technology *	Direct thermal	Storage temperature (T-T)	-10 - 50 °C
Type *	POS printer	Operating relative humidity (H-H)	10 - 90%
Paper handling		Storage relative humidity (H-H)	10 - 90%
Maximum roll diameter	8.3 cm	Weight & dimensions	
Supported paper width	80 mm	Width	125 mm
Ports & interfaces		Depth	194 mm
USB port *	✓	Height	114 mm
USB connector	USB Type-B	Weight	1.7 kg
Connectivity technology *	Wired	Packaging data	
Standard interfaces	Ethernet, USB 2.0	Quantity per pack	1 pc(s)
Network		Package width	195 mm
Ethernet LAN *	✓	Package depth	255 mm
Features		Package height	245 mm
Sound pressure level (printing)	55 dB	Package weight	2.86 kg
Mean time between failures (MTBF)	360000 h	Print technology	
Half-cutter	✓	Column capacity	56/42
Autocutter durability	1.7 million cuts	Logistics data	
Print head life	120 km	Harmonized System (HS) code	84433210
Country of origin	China	Technical details	
Safety	DE, TÜV, GOST-R	Changeable interface	✓
Certification	CE, GOST-R, EN55022-Class A	Other features	
Design		Buffer size	4 KB
Product colour *	Grey	Electromagnetic compatibility	CE marking, GOST-R, EN55022 Class A
Power		Mean cycles between failures (MCFB)	6500000
Power source type *	AC	Print head life	120 Impulse
AC input voltage	24 V		



8715946620480

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-JUN-2023. Prints or copies of Information are only valid on the printed Publication date