EPSON
EXCEED YOUR VISION

Epson WorkForce DS-1660W Flatbed scanner 600 x 600 DPI A4 Black, White

Brand : Epson   **Product family:** WorkForce   **Product code:** B11B244401BY

Product name : DS-1660W

A4, Flatbed, 600 x 600DPI, ReadyScan LED, 25ppm, USB 3.0, Wireless LAN IEEE 802.11a/b/g/n, Wi-Fi Direct
Epson WorkForce DS-1660W. Maximum scan size: 210 x 3048 mm, Optical scanning resolution: 600 x 600 DPI, Enhanced scan resolution: 1200 x 1200 DPI. Scanner type: Flatbed scanner, Product colour: Black, White, Display: LCD. Daily duty cycle (max): 1500 pages, Light source: ReadyScan LED, Scan file formats: PDF, TIFF. Auto document feeder (ADF) input capacity: 50 sheets. Maximum ISO A-series paper size: A4, ISO A-series sizes (A0...A9): A4, A5, A6, ISO B-series sizes (B0...B9): B5

ENERGY STAR

Scanning

Maximum scan size *	210 x 3048 mm
Optical scanning resolution *	600 x 600 DPI
Enhanced scan resolution	1200 x 1200 DPI
Colour scanning	✔
Duplex scanning *	✔
ADF scan speed (b/w, A4)	25 ppm
ADF scan speed (colour, A4)	25 ppm

Design

Scanner type *	Flatbed scanner
Product colour *	Black, White
Display	LCD
Built-in display *	✔

Performance

Light source	ReadyScan LED
Scan file formats	PDF, TIFF
Daily duty cycle (max) *	1500 pages
Scan drivers	TWAIN
Scanning noise level	55 dB

Input capacity

Auto document feeder (ADF) input capacity	50 sheets

Paper handling

Maximum ISO A-series paper size *	A4
ISO A-series sizes (A0...A9)	A4, A5, A6
ISO B-series sizes (B0...B9)	B5
Letter	✔
Legal	✔
Maximum scan area (ADF)	210 x 3048 mm
Minimum scan area (ADF)	89 x 127 mm

Ports & interfaces

USB port *	✔
USB version	3.2 Gen 1 (3.1 Gen 1)
Optional connectivity	Ethernet
Standard interfaces	USB 3.2 Gen 1 (3.1 Gen 1), Wireless LAN

Power

Power supply type *	AC

Network

Wi-Fi	✔
Wi-Fi standards	802.11a, 802.11b, 802.11g
Ethernet LAN	✔
Supported network protocols	TCP/IP, DHCP, DNS, SNMP, SLP

System requirements

Windows operating systems supported	✔

Operational conditions

Operating temperature (T-T)	10 - 35 °C
Storage temperature (T-T)	-20 - 80 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	20 - 80%

Weight & dimensions

Width	451 mm
Depth	315 mm
Height	120 mm

Packaging content

Cables included	AC, USB

Technical details

Sustainability certificates	ENERGY STAR

Logistics data

Harmonized System (HS) code	84716070

8715946605654