



## DELL 403-BBLR interface cards/adapter Internal Fiber

Brand : DELL

Product code: 403-BBLR

Product name : 403-BBLR



Emulex LPe31002-M6-D Dual Port 16Gb Fibre Channel HBA, Low Profile

[DELL 403-BBLR interface cards/adapter Internal Fiber:](#)

Emulex LPe31002-M6-D Low Profile Dual Port 16Gb Fibre Channel HBA with 16Gb FC connectivity (short wave optical - LC SFP+ included) from Dell™ are designed to address the demanding performance, reliability and management requirements of modern networked storage systems that utilize high performance and low latency solid state storage drives and HDD arrays. Compared to the previous generation, they provide up to 2x greater bandwidth, less than half the latency, and new features such as Forward Error Correction and enhanced diagnostics and I/O monitoring capabilities.



Ports & interfaces		Technical details	
Host interface *	PCIe	Sustainability certificates	RoHS
Output interface *	Fiber	<b>Packaging data</b>	
Expansion card form factor	Low-profile	Quantity	1
Expansion card standard	PCIe 3.0	<b>Logistics data</b>	
<b>Design</b>		Harmonized System (HS) code	84733020
Internal *	✓	<b>Other features</b>	
Product colour	Green	Data transfer rate	14.025 Gbit/s
Purpose	Server	Ports quantity	2
Certification	CSA, UL, FCC, RoHS, TUV Bauart, BSMI Class A, ICES Class A, VCCI Class A, MSIP Class A, China RoHS, RCM	Data link protocols	16Gb Fibre Channel
<b>Operational conditions</b>		Connectivity technology	Wired
Operating temperature (T-T)	0 - 55 °C	Compatible operating systems	SUSE Linux Enterprise Server, Microsoft Windows, Red Hat Enterprise Linux
Operating relative humidity (H-H)	5 - 95%	- PowerEdge VRTX - PowerEdge R630 - PowerEdge R730 - PowerEdge R730XD - PowerEdge R530 - PowerEdge FC430 - PowerEdge FC630 - PowerEdge FC830 - PowerEdge R630XL - PowerEdge R730XL - PowerEdge R730xd XL - Poweredge R830 - PowerEdge R640 - PowerEdge R740 - PowerEdge R740XD - PowerEdge R440 - PowerEdge R540 - PowerEdge FC640 - PowerEdge R6415 - PowerEdge R7415 - PowerEdge R7425 - PowerEdge R840 - PowerEdge R940xa - PowerEdge R6515 - PowerEdge R7515	
<b>System requirements</b>		Compatibility	
Windows operating systems supported	✓		
Linux operating systems supported	✓		




5397063983698



5711783355410



0884116383307



884116383307

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.