

StarTech.com 4 Port USB 3.0 Hub - USB Type-A Hub with 1x USB-C & 3x USB-A (SuperSpeed 5Gbps) - USB Bus or Self-Powered - Portable USB 3.1/3.2 Gen 1 BC 1.2 Charging Hub w/ Power Adapter

Brand : StarTech.com

Product code: HB30A3A1CSFS

Product name : 4 Port USB 3.0 Hub - USB Type-A Hub with 1x USB-C & 3x USB-A (SuperSpeed 5Gbps) - USB Bus or Self-Powered - Portable USB 3.1/3.2 Gen 1 BC 1.2 Charging Hub w/ Power Adapter

StarTech.com 4 Port USB 3.0 Hub - USB Type-A Hub with 1x USB-C & 3x USB-A (SuperSpeed 5Gbps) - USB Bus or Self-Powered - Portable USB 3.1/3.2 Gen 1 BC 1.2 Charging Hub w/ Power Adapter (HB30A3A1CSFS)

StarTech.com 4 Port USB 3.0 Hub - USB Type-A Hub with 1x USB-C & 3x USB-A (SuperSpeed 5Gbps) - USB Bus or Self-Powered - Portable USB 3.1/3.2 Gen 1 BC 1.2 Charging Hub w/ Power Adapter. Host interface: USB 3.2 Gen 1 (3.1 Gen 1) Type-A, Hub interfaces: USB 3.2 Gen 1 (3.1 Gen 1) Type-A, USB 3.2 Gen 1 (3.1 Gen 1) Type-C. Data transfer rate: 5000 Mbit/s, Product colour: Black, Housing material: Plastic. Input voltage: 100 - 240 V, Input current: 1 A, Output voltage: 5 V. Width: 74 mm, Depth: 38 mm, Height: 13 mm. Package width: 165 mm, Package depth: 49 mm, Package height: 131 mm



Ports & interfaces		Weight & dimensions	
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-A	Height	13 mm
Hub interfaces *	USB 3.2 Gen 1 (3.1 Gen 1) Type-A, USB 3.2 Gen 1 (3.1 Gen 1) Type-C	Weight	39 g
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3	Packaging data	
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1	Package width	165 mm
Ports quantity *	4	Package depth	49 mm
Features		Package height	131 mm
Data transfer rate *	5000 Mbit/s	Package weight	376 g
Product colour	Black	Packaging content	
Housing material	Plastic	AC adapter included	✓
Cable length	0.146 m	Included power plug types	AU, EU, NA, UK
Plug and Play	✓	Operational conditions	
Certification	RoHS, CE, FCC, TAA	Operating temperature (T-T)	0 - 60 °C
Power		Storage temperature (T-T)	-20 - 60 °C
Input voltage	100 - 240 V	Operating relative humidity (H-H)	0 - 90%
Input current	1 A	Logistics data	
Output voltage	5 V	Master (outer) case width	284 mm
Output current	4 A	Master (outer) case length	342 mm
Power plug type	Type B	Master (outer) case height	302 mm
Weight & dimensions		Products per master (outer) case	20 pc(s)
Width	74 mm	Harmonized System (HS) code	84719000
Depth	38 mm	Other features	
		Chipset	Genesys Logic - GL3522



0065030866118



065030866118

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.