



Lindy 1m DisplayPort to HDMI 10.2G Cable

Brand : Lindy

Product code: 36921

Product name : 1m DisplayPort to HDMI 10.2G Cable

1m DisplayPort to HDMI 10.2G Cable

[Lindy 1m DisplayPort to HDMI 10.2G Cable:](#)

Connects a DisplayPort equipped device to a 4K UHD HDMI display or projector
Supports resolutions up to 3840x2160@30Hz
Supports video mirroring and extended desktop modes
Audio pass-through if supported by the video source
2 year warranty

The Lindy DisplayPort to HDMI Cable is ideal for connecting a DisplayPort equipped source such as a PC or laptop to an HDMI display. Supporting 4K UHD resolutions up to 3840x2160@30Hz, this cable is ideal for ensuring video is displayed in superior clarity. This cable can also be used to add another display to extend the available desktop workspace and increase productivity, great for use in residential or workplace office setups.

The DisplayPort to HDMI Cable supports uncompressed 7.1 Audio and compressed Audio such as DTS-HD Master Audio, Dolby TrueHD. Please note that audio output over HDMI is only supported when the graphics card of the laptop or desktop computer supports audio output over DisplayPort.



Features		Features	
Connector 1 form factor	Straight	Contact material	Copper
Connector 2 form factor	Straight	AWG wire size	28
Connector contacts plating	Gold	Colour depth	8 bit
Cable length *	1 m	Colour sampling	4:4:4
Connector 1 *	DisplayPort	Cable shielding	Aluminium braid
Connector 2 *	HDMI Type A (Standard)	Certification	CE, UKCA, FCC, RoHS, REACH, UL, California Proposition 65
Connector 1 gender *	Male	Operational conditions	
Connector 2 gender *	Male	Operating temperature (T-T)	0 - 45 °C
HDMI version	1.4	Storage temperature (T-T)	-10 - 80 °C
DisplayPort version	1.2	Weight & dimensions	
Maximum resolution	3840 x 2160 pixels	Cable diameter	7.3 mm
Supported video modes	1080p	Connector 1 dimensions (WxDxH)	36.4 x 20.5 x 9.4 mm
Data transfer rate	10.2 Gbit/s	Connector 2 dimensions (WxDxH)	37.5 x 20.5 x 10.5 mm
Bend radius (min)	7.3 cm	Packaging data	
Product colour	Black	Quantity per pack	1 pc(s)
Conductor material	Tinned copper	Package type	Polybag
Nominal attenuation	100MHz~450MHz -2.44~-5.099dB 450MHz~8100MHz -5.094~32.906dB	Logistics data	
Jacket material	Polyvinyl chloride (PVC)	Harmonized System (HS) code	84733080
Cable type	Round cable		
Connector housing material	Polyvinyl chloride (PVC) / Acrylonitrile butadiene styrene (ABS)		



4002888369213

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 06-APR-2023. Prints or copies of Information are only valid on the printed Publication date