Viewsonic PA503S data projector Standard throw projector 3600 ANSI lumens DLP SVGA (800x600) Grey, White

Brand : Viewsonic Product code: PA503S

Product name : PA503S

 800×600 , DLP, 3600 ANSI lum, 30-300", 190 W, 4:3, Mini USB B, RS-232, RCA, 3.5mm, HDMI 1.4, VGA, $2\times$ RGB, 2 W RMS, $294\times218\times110$ mm

Viewsonic PA503S. Projector brightness: 3600 ANSI lumens, Projection technology: DLP, Projector native resolution: SVGA (800x600). Light source type: Lamp, Service life of light source: 4500 h, Service life of light source (economic mode): 15000 h. Focus: Manual, Zoom type: Manual, Optical zoom: 1.1x. Analog signal format system: NTSC, PAL, PAL 60, SECAM, Supported graphics resolutions: 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA),..., Supported video modes: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p. Serial interface type: RS-232, HDMI connector type: Full-size





Projector Network X Screen size compatibility* 762 - 7620 mm (30 - 300") Wi-Fi* X Projection distance 1.1 - 13 m Storage Projector brightness** 3600 ANSI lumens Card reader integrated** X Projector native resolution* SVGA (800×600) Features FCC (ICES-003), cTUVus Native aspect ratio** 4.3 Certification FCC (ICES-003), cTUVus Number of colours 1.073 billion colours Multimedia Horizontal scan range 15 - 102 kHz Built-in speaker(s)* ✓ Vertical scan range 23 - 120 Hz Built-in speaker(s)* ✓ Keystone correction, vertical 40 - 40° Mumber of built-in speakers 1 Matrix size 1.4 cm (0.55") Mumber of built-in speakers 1 Light source Lamp Product type* Standard throw projector Eight source Lamp Product colour* Grey, White Light source 450 0 h Cable lock slot Standard throw projector Service life of light source 15000 h Ca				
Projection distance 1.1 · 13 m Storage Projector brightness* 3600 AMSI lumens Card reader integrated *	Projector		Network	
Projector brightness* 3600 ANSI lumens Storage Projection technology* DLP Card reader integrated ** ★ Projection tackive resolution * SVGA (800x600) Features FCC (ICES-03), cTUVus Native aspect ratio * 4.3 Certification FCC (ICES-03), cTUVus Number of colours 1.073 billion colours Multimedia Horizontal scan range 15 - 102 kHz Built-in speaker(s) * ✓ Keystone correction, vertical -40 - 40° RMS rated power 2 W Keystone correction, vertical -40 - 40° Number of built-in speakers 1 Matrix size DND Design Tumber of built-in speakers 1 Matrix size Lamp Product colour * Standard throw projector Light source type * Lamp Product colour * Desktop Service life of light source 4500 h Cable lock slot type Kensington Lamp power 1 lamp(s) Built-in display * X Less system Power AC Focus * Manual Power source *	' '	762 - 7620 mm (30 - 300")	Wi-Fi *	×
Projection technology* DLP Card reader integrated ** X Projector native resolution ** SVGA (800x600) Features Native aspect ratio ** 43 Certification FCC (ICES-003), cTUVus Number of colours 1.073 billion colours Multimedia Horizontal scan range 15 - 102 kHz Built-in speaker(s) * ✓ Keystone correction, vertical 40 - 40° RMS rated power 2 W Keystone correction, vertical 40 - 40° Number of built-in speakers 1 Matrix size 1.4 cm (0.55°) Design V Light source Lamp Product type * Standard throw projector Light source 4500 h Cable lock slot ✓ Service life of light source 4500 h Cable lock slot ✓ Ceconomic mode) 15000 h Cable lock slot ✓ Lamp power 19 W Display X Lems system Manual Power source * AC Coor capability ✓ Power consumption (typical) * 260 W	•		Storage	
Projector native resolution * SVGA (800x600) Features Native aspect ratio * 4:3 Certification FCC (ICES-003), cTUVus Number of colours 1.073 billion colours Multimedia Horizontal scan range 15 - 102 kHz Built-in speaker(s) * ✓ Keystone correction, vertical 40 - 40° Mumber of built-in speakers 1 Matrix stype DMO Design Indicate throw projector Matrix stype Lamp Product type * Standard throw projector Eight source Lamp Product colour * Grey, White Service life of light source * 4500 h Cable lock slot ✓ Service life of light source (economic mode) 15000 h Cable lock slot ✓ Lamp power 190 W Display X Leams system Power Power Focus * Manual Power source * AC Zoom type Manual Power consumption (typical) * 260 W Optical zoom 1.1x AC input trequency 50 - 60 Hz Video	, ,		Card reader integrated *	×
Native aspect ratio * 4:3 Certification FCC (ICES-003), cTUVus Number of colours 1.073 billion colours Multimedia Horizontal scan range 15 - 102 kHz Built-in speaker(s) * ✓ Vertical scan range 23 - 120 Hz RMS rated power 2 W Keystone correction, vertical -40 - 40° Number of built-in speakers 1 Matrix size 1.4 cm (0.55°) Number of built-in speakers 1 Matrix size DMD Design Standard throw projector Light source Froduct colour * Standard throw projector Placement Desktop Grey, White Placement Desktop Desktop Lamp Placement Desktop Desktop Lamp sequantity 190 W Suiple lock slot type Kensington Lamp squantity 1 lamp(s) Built-in display * X Focus * Manual Power AC Zoom capability ✓ Power sonsumption (typical) * 260 W Zoom tapability ✓ Power sonsumption (typical) *	,		Features	
Notizental scan range	•		Certification	FCC (ICES-003), cTUVus
Horizontal scan range	Number of colours	1.073 billion colours	Multimedia	
Vertical scan range 23 - 120 Hz RMS rated power 2 W Keystone correction, vertical -40 - 40° Number of built-in speakers 1 Matrix type DMD Design Standard throw projector Light source Product type * Standard throw projector Light source type * Lamp Product colour * Grey, White Service life of light source * 4500 h Cable lock slot Jesktop Service life of light source (economic mode) 15000 h Cable lock slot type Kensington Lamp power 190 W Display X Lamp squantity 1 lamp(s) Built-in display * X Lens system Manual Power Y Focus * Manual Power source * AC Zoom capability Y Power consumption (typical) * 260 W Zoom type Manual Power consumption (standby) * 0.5 W Video Standard throw projector Forestain AC In your consumption (standby) * 0.5 W W Cond	Horizontal scan range	15 - 102 kHz		1
Keystone correction, vertical -40 - 40° Number of built-in speakers 1 Matrix size 1.4 cm (0.55°) Number of built-in speakers 1 Light source Product type * Standard throw projector Light source type * Lamp Product colour * Grey, White Service life of light source (economic mode) 4500 h Cable lock slot type Kensington Lamp power 190 W Display Lamps quantity Lamp squantity I lamp(s) Built-in display * X Lens system Power Power Focus * Manual Power source * AC Zoom capability V Power consumption (typical) * 260 W Zoom type Manual Power consumption (standby) * 0.5 W Optical zoom 1.1x AC input voltage 100 - 240 V Video Supplier features Analog signal format system * NTSC, PAL, PAL 60, SECAM Harmonized System (HS) code 85286200 85286200 Supported graphics resolution AC Operating altitude Operating altitude	Vertical scan range		• • • • • • • • • • • • • • • • • • • •	
Matrix size 1.4 cm (0.55°) Design Light source Product type * Standard throw projector Light source type * Lamp Product colour * Grey, White Light source type * Lamp Product colour * Grey, White Light source (eff light source (economic mode) 4500 h Cable lock slot Jesktop Service life of light source (economic mode) 15000 h Cable lock slot type Kensington Lamp power 190 W Display Lems system Kensington Lems system Power Power Focus * Manual Power source * AC Zoom capability Interpretation of typical of t	•		•	
Light source Product type * Standard throw projector Light source type * Lamp Product colour * Grey, White Service life of light source (economic mode) 4500 h Cable lock slot ✓ Service life of light source (economic mode) 15000 h Cable lock slot type Kensington Lamp power 190 W Display X Lamps quantity 1 lamp(s) Built-in display * X Lens system Power Power Focus * Manual Power source * AC Zoom capability ✓ Power consumption (typical) * 260 W Zoom type Manual Power consumption (standby) * 0.5 W Optical zoom 1.1x AC input voltage 100 - 240 V Throw ratio 1.96 - 2.15:1 AC input requency 50 - 60 Hz Video Supplier features Analog signal format system * NTSC, PAL, PAL 60, SECAM Harmonized System (HS) code 85286200 Supported graphics resolutions 756, 800 x 600 (SVGA), 1280 x 800 (WXGA), 1280 x 1024 (SXGA), 128			·	
Product colour * Grey, White Cable lock slot Placement Desktop		ОМО		Standard throw projector
Light source type * Lamp Placement Desktop Service life of light source (economic mode) 15000 h Cable lock slot type Kensington Lamp power 190 W Display X Lamps quantity 1 lamp(s) Built-in display * X Lens system Power AC Focus * Manual Power source * AC Zoom capability ✓ Power consumption (typical) * 260 W Zoom type Manual Power consumption (typical) * 0.5 W Optical zoom 1.1x AC input voltage 100 - 240 V Throw ratio 1.96 - 2.15:1 AC input frequency 50 - 60 Hz Video Supplier features Analog signal format system * NTSC, PAL, PAL 60, SECAM Harmonized System (HS) code 85286200 3D Ready Foreating altivate Operating temperature (T-T) 0 - 40 °C Volume to divide modes Volume to divide modes Operating altitude 0 - 1499 m Supported graphics resolutions 480i, 480p, 576i, 576p, 720p, 1080i, Weight & dimensions				' '
Service life of light source (economic mode) 15000 h Cable lock slot type Kensington Lamp power 190 W Display Lamps quantity 1 lamp(s) Built-in display * X Lens system Power Focus * AC Zoom capability Younger consumption (typical) * 260 W Zoom type Manual Power consumption (standby) * 0.5 W Optical zoom 1.1x AC input voltage 100 - 240 V Throw ratio 1.96 - 2.15:1 AC input frequency 50 - 60 Hz Video Supplier features Analog signal format system * NTSC, PAL, PAL 60, SECAM Harmonized System (HS) code 85286200 3D Ready Younger features Harmonized System (HS) code 85286200 Supported graphics resolutions 576, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 768 (WXGA), 1280 x 768 (WXGA), 1366 x 768 (WXGA), 1366 x 768 (WXGA), 1366 x 768 (WXGA), 1366 x 768 (WXGA), 1360 x 768 (WXGA), 1360 x 768 (WXGA), 1360 x 768 (WXGA), 1440 x 900 (WXGA), 1400 x 1050 (SXGA+), 1440 x 900 (WXGA), 1400 x 1050 x 100 x 100 x 100 x 100 x 100	J ,,	•		•
(economic mode) 15000 h Cable lock slot type Kensington Lamp power 190 W Display ★ Lamps quantity 1 lamp(s) Built-in display * ★ Lens system Power Focus * AC Zoom capability ✓ Power consumption (typical) * 260 W Zoom type Manual Power consumption (standby) * 0.5 W Optical zoom 1.1x AC input voltage 100 - 240 V Throw ratio 1.96 - 2.15:1 AC input frequency 50 - 60 Hz Video Supplier features Harmonized System (HS) code 85286200 3D Ready ✓ Operational conditions Operational conditions Supported graphics resolutions 756, 800 x 600 (SVGA), 1224 x 768 (XGA), 1280 x 768 (WGA), 1280 x 1024 (SXGA), 1280 x 768 (WGA), 1366 x 768, 1400 x 1050 (SXGA+), 1440 x 900 (WXGA), 1366 x 768, 1400 x 1050 (SXGA+), 1440 x 900 (WXGA), 1360 x 768 (WGA), 1280 x 1024 x	•	4500 h	Cable lock slot	√
Lamps quantity 1 lamp(s) Built-in display * X Lens system Power Focus * Manual Power source * AC Zoom capability ✓ Power consumption (typical) * 260 W Zoom type Manual Power consumption (standby) * 0.5 W Optical zoom 1.1x AC input voltage 100 - 240 V Throw ratio 1.96 - 2.15:1 AC input frequency 50 - 60 Hz Video Supplier features Analog signal format system * NTSC, PAL, PAL 60, SECAM Harmonized System (HS) code 85286200 3D Ready ✓ Operational conditions Operating temperature (T-T) 0 - 40 °C Supported graphics resolutions 76, 800 x 600 (SVGA), 1280 x 768, (XGA), 1290 x 1200 (WUXGA), 1240 x 1440 x 900 (WUXGA), 1240 x 1440 x 900 (WUXGA), 1240 x 1240 (WUXGA) Operating altitude 0 - 1499 m Supported video modes 480i, 480p, 576i, 576p, 720p, 1080i, Width Weight & dimensions 294 mm		15000 h	Cable lock slot type	Kensington
Descripted video modes Power Power	Lamp power	190 W	Display	
Focus * Manual Power source * AC Zoom capability	Lamps quantity	1 lamp(s)	Built-in display *	×
Zoom capability V Power consumption (typical) * AC Zoom type Manual Power consumption (typical) * 260 W Optical zoom 1.1x AC input voltage 100 - 240 V Throw ratio 1.96 - 2.15:1 AC input frequency 50 - 60 Hz Video Supplier features Analog signal format system * NTSC, PAL, PAL 60, SECAM Harmonized System (HS) code 85286200 3D Ready 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 702 (HD 720), 1280 x 800 (WXGA), 1280 x 702 (HD 720), 1280 x 800 (WXGA), 1366 x 768 (WXGA), 1360 x 768 (WXGA),	Lens system		Power	
Zoom type	Focus *	Manual	Power source *	AC
Optical zoom 1.1x	Zoom capability	✓	Power consumption (typical) *	260 W
Throw ratio 1.96 - 2.15:1 AC input frequency 50 - 60 Hz Supplier features Analog signal format system * Analog signal format system * NTSC, PAL, PAL 60, SECAM 640 × 480 (VGA), 720 × 480, 720 × 576, 800 × 600 (SVGA), 1024 × 768 (XGA), 1280 × 1024 (SXGA), 1280 × 720 (HD 720), 1280 × 800 (WXGA), 1360 × 768 (WXGA), 1366 × 768, 1400 × 1050 (SXGA+), 1440 × 900 (WXGA+), 1920 × 1200 (WUXGA) Supported video modes AC input frequency 50 - 60 Hz Parmonized System (HS) code 85286200 Operating temperature (T-T) O - 40 °C Operating relative humidity (H-H) Operating altitude Veight & dimensions Weight & dimensions Width 294 mm	• •		Power consumption (standby) *	0.5 W
Video Supplier features Analog signal format system * NTSC, PAL, PAL 60, SECAM Harmonized System (HS) code 85286200 3D Ready 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 768 (WAGA), 1280 x 700 (HD 720), 1280 x 800 (WXGA), 1360 x 768 (WXGA), 1360 x 768 (WXGA), 1366 x 768, 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+), 1920 x 1200 (WUXGA) Operating temperature (T-T) 0 - 40 °C Operating relative humidity (H-H) 10 - 90% Operating altitude Operating altitude 0 - 1499 m Supported video modes 480i, 480p, 576i, 576p, 720p, 1080i, Weight & dimensions 294 mm	•		AC input voltage	100 - 240 V
Analog signal format system * NTSC, PAL, PAL 60, SECAM Harmonized System (HS) code 85286200 Operational conditions Operating temperature (T-T) 0 - 40 °C (XGA), 1280 x 1024 (SXGA), 1280 x (SVGA), 1280 x 720 (HD 720), 1280 x 800 (WXGA), 1366 x 768, 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+), 1920 x 1200 (WUXGA) Supported video modes NTSC, PAL, PAL 60, SECAM Harmonized System (HS) code 85286200 Operational conditions Operating temperature (T-T) 0 - 40 °C Operating relative humidity (H-H) 10 - 90% Operating altitude 0 - 1499 m Weight & dimensions Width 294 mm		1.96 - 2.15:1	AC input frequency	50 - 60 Hz
3D Ready 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 800 (WXGA), 1360 x 768 (WXGA), 1366 x 768, 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+), 1920 x 1200 (WUXGA) 480i, 480p, 576i, 576p, 720p, 1080i, Supported video modes 70 (HD 720), 1280 x 800 (WXGA) 1360 x 768 (WXGA), 1366 x 768, 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+), 1920 x 1200 (WUXGA) 480i, 480p, 576i, 576p, 720p, 1080i, Width 70 (HS) code 9220020 Operational conditions Operating temperature (T-T) 0 - 40 °C Operating relative humidity (H-H) 10 - 90% Operating altitude 0 - 1499 m Weight & dimensions Width 294 mm			Supplier features	
Supported graphics resolutions 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 800 (WXGA), 1360 x 768 (WXGA), 1366 x 768, 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+), 1920 x 1200 (WUXGA) Supported video modes 640 x 480 (VGA), 720 x 480, 720 x 800 (Deprating temperature (T-T) (Deprating relative humidity (H-H) (Deprating altitude (,		Harmonized System (HS) code	85286200
Supported graphics resolutions 576, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 768 (XGA), 1280 x 800 (WXGA), 1280 x 800 (WXGA), 1360 x 768 (WXGA), 1366 x 768, 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+), 1920 x 1200 (WUXGA) 480i, 480p, 576i, 576p, 720p, 1080i, 576i, 576i,	3D Ready	640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 800 (WXGA), 1360 x 768 (WXGA), 1366 x 768, 1400 x 1050 (SXGA+), 1440 x 900	Operational conditions	
Supported graphics resolutions 720 (HD 720), 1280 x 800 (WXGA), 1360 x 768 (WXGA), 1366 x 768, 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+), 1920 x 1200 (WUXGA) 480i, 480p, 576i, 576p, 720p, 1080i, 576i, 576p, 720p, 576i, 576p, 720p, 576i, 576p, 720p,	Supported graphics resolutions		Operating temperature (T-T)	0 - 40 °C
1360 x 768 (WXGA), 1366 x 768, 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+), 1920 x 1200 (WUXGA) 480i, 480p, 576i, 576p, 720p, 1080i, Width 294 mm			Operating relative humidity (H-H)	10 - 90%
(WXGA+), 1920 x 1200 (WUXGA) 480i, 480p, 576i, 576p, 720p, 1080i, Width 294 mm			Operating altitude	0 - 1499 m
Supported video modes 480i, 480p, 576i, 576p, 720p, 1080i, Width 294 mm			Weight & dimensions	
1080p Depth 110 mm	Supported video modes		Width	294 mm
	Supported video modes	1080p	Depth	110 mm

Ports & interfaces		Weight & dimensions	
HDMI connector type	Full-size	Height	218 mm
HDMI version	1.4	Weight *	2.2 kg
Serial interface type *	RS-232	Package width	365 mm
PC Audio in	✓	Package depth	188 mm
PC Audio out	✓	Package height	300 mm
VGA (D-Sub) ports quantity *	3	Package weight	3.24 kg
HDMI ports quantity *	1	Packaging content	
Composite video in *	1	Remote control included *	1
DVI port *	×	Cables included	AC, VGA
AC (power) in	✓	Quick start guide	√
Network		, ,	*
Ethernet LAN *	u	Other features	
Luiemet Lan	×	RS-232 ports	1





766907904710

0766907904710

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.