
D-Link 1000Base-LX Mini Gigabit Interface Converter network switch component

Brand : D-Link

Package weight

Product code: DEM-310GT



Gigabit Interface Converter DEM-310GT


D-Link 1000Base-LX Mini Gigabit Interface Converter network switch component:

64 g

D-Link's new line of Gigabit Interface Converters (GBICs) and Small Form-Factor Pluggables (SFPs) transceivers represent an industry leading combination of performance and affordability. D-Link's new Gigabit transceivers are available in two form-factors: standard (GBIC) or (SFP)/mini-GBIC. The DEM-310GT is a high performance 1310nm multimode/Singlemode SFP (mini-GBIC) transceiver. Supporting full duplex, Gigabit speeds on multimode/Singlemode fiber for distances of up to 550m/550m/10km on 62.5µm/50µm/9µm respectively. The unit features a metal housing to reduce EMI and to increase durability. The DEM-310GT is hot pluggable and is backed by a standard 3-year product warranty and free technical support.

Features		Technical details	
Product colour Internal Harmonized System (HS) code Network Data transfer rate Data link protocols Cabling technology	Stainless steel ✓ 85177900 1 Gbit/s Gigabit Ethernet 1000Base-LX	Shipping (inner) case length Shipping (inner) case width Shipping (inner) case width Shipping (inner) case height Shipping (inner) case net weight Products per shipping (inner) case Pallet gross weight (air) Master (outer) cases per pallet (air) Products per pallet (air) Products per pallet (air) Pallet gross length Pallet gross width Pallet height (air) Pallet gross weight (sea)	36 cm 26 cm 31 cm 3.2 kg 50 pc(s) 246.8 kg 54 pc(s) 2700 pc(s) 102 cm 122 cm 199 cm 246.8 kg
Compliance industry standards Operational conditions	802.3z		
Operating temperature (T-T) Storage temperature (T-T)	0 - 70 °C -40 - 85 °C		
Weight & dimensions		Master (outer) cases per pallet (sea)	1 1 1
Dimensions (WxDxH) Ports & interfaces	29.8 x 11.8 x 56.3 mm	Products per pallet (sea) Pallet height (sea) Shipping (inner) case gross weight	2700 pc(s) 199 cm 4.2 kg
I/O ports	mini-GBIC		
Technical details			
Technical features Package depth Package width Package height	Optical Receiver Sensitivity -20dBm 131 mm 74 mm 49 mm		











Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.