



## APC SMT1500RM2UC uninterruptible power supply (UPS) Line-Interactive 1.44 kVA 1000 W 6 AC outlet(s)



Brand : APC

Product code: SMT1500RM2UC

Product name : SMT1500RM2UC

Smart-UPS 1500VA, LCD, RM 2U, 120V with SmartConnect

APC SMT1500RM2UC. UPS topology: Line-Interactive, Output power capacity: 1.44 kVA, Output power: 1000 W. AC outlet types: NEMA 5-15R, Power plug: NEMA 5-15P, AC outlets quantity: 6 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 6 year(s), Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 432 mm, Depth: 477 mm, Height: 86 mm

Features		Battery	
UPS topology *	Line-Interactive	Battery life (max)	6 year(s)
Output power capacity *	1.44 kVA	Battery recharge time	3 h
Output power *	1000 W	Hot-swap battery	✓
Waveform *	Sine	Automatic battery test	✓
Input operation voltage (min) *	75 V	Cold start	✓
Input operation voltage (max) *	154 V		
Input frequency *	50/60 Hz		
Output operation voltage (min)	110 V		
Output operation voltage (max)	127 V		
Automatic Voltage Regulation (AVR)	✓		
Surge energy rating	680 J		
Response time	10 ms		
EMI/RFI noise filtering	✓		
Noise level	45 dB		
Power protection features	Short circuit		
Audible alarm(s)	✓		
Web-based management	✓		
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm		
Auto-restart	✓		
Ports & interfaces		Design	
AC outlet types	NEMA 5-15R	Form factor *	Rackmount
Power plug	NEMA 5-15P	Rack capacity	2U
AC outlets quantity	6 AC outlet(s)	Cable length	2.44 m
USB port	✓	Product colour *	Black
Serial interface	✓	Display type	LCD
SmartSlot	✓	LED indicators	Status
		Certification	REACH
Battery		Operational conditions	
Battery technology	Sealed Lead Acid (VRLA)	Operating temperature (T-T)	0 - 40 °C
Number of batteries supported	1	Storage temperature (T-T)	-15 - 45 °C
		Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
		Technical details	
		Sustainability certificates	RoHS, ENERGY STAR
		Weight & dimensions	
		Width	432 mm
		Depth	477 mm
		Height	86 mm
		Weight	26.5 kg
		Package width	590 mm
		Package depth	610 mm
		Package height	235 mm
		Package weight	32.1 kg
		Logistics data	
		Harmonized System (HS) code	85078000



0731304322801



731304322801

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.