

D-Link DGS-1210-16 network switch Managed L2 Black

Brand : D-Link

Product code: DGS-1210-16

Product name : DGS-1210-16



16-port Gigabit Smart Switch, including 4 Combo SFP ports

D-Link DGS-1210-16. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports quantity: 12. Full duplex. MAC address table: 8000 entries, Switching capacity: 32 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Power connector: DC-in jack. Rack mounting

Management features		Technical details	
Switch type *	Managed	Shipping (inner) case length	38.2 cm
Switch layer	L2	Shipping (inner) case net weight	15 kg
Quality of Service (QoS) support	✓	Products per shipping (inner) case	5 pc(s)
Web-based management	✓	Pallet gross weight (air)	445.7 kg
System event log	✓	Master (outer) cases per pallet (air)	27 pc(s)
MIB support	1213 MIB II, 1493 Bridge MIB, 1907 SNMP v2 MIB, 1215 Trap Convention MIB, 2233 Interface Group MIB, D-Link Private MIB	Products per pallet (air)	135 pc(s)
Ports & interfaces		Pallet gross length	110 cm
Basic switching RJ-45 Ethernet ports quantity *	12	Pallet gross width	120 cm
Combo SFP ports quantity	4	Pallet height (air)	129.3 cm
SFP/SFP+ slots quantity	4	Pallet gross weight (sea)	730.4 kg
Power connector	DC-in jack	Master (outer) cases per pallet (sea)	45 pc(s)
Network		Products per pallet (sea)	225 pc(s)
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Pallet height (sea)	2.06 m
Copper ethernet cabling technology	1000BASE-T, 100BASE-TX, 10BASE-T	Shipping (inner) case gross weight	15.8 kg
Port mirroring	✓	Power	
Full duplex	✓	Input voltage	100 - 240 V
Flow control support	✓	Power consumption (typical)	17.4 W
Link aggregation	✓	Power over Ethernet (PoE)	
Broadcast storm control	✓	Power over Ethernet (PoE) *	✗
Auto MDI/MDI-X	✓	Operational conditions	
Spanning tree protocol	✓	Operating temperature (T-T)	0 - 40 °C
Head-of-line (HOL) blocking	✓	Storage temperature (T-T)	-10 - 70 °C
Number of VLANs	256	Operating relative humidity (H-H)	10 - 95%
Data transmission		Storage relative humidity (H-H)	5 - 95%
Switching capacity *	32 Gbit/s	Heat dissipation	59.23 BTU/h
MAC address table *	8000 entries	Weight & dimensions	
Store-and-forward	✓	Weight	2.87 kg
Maximum data transfer rate	1 Gbit/s	Packaging data	
Packet buffer memory	0.5 MB	Package width	357 mm
Security		Package depth	331 mm
DHCP features	DHCP client	Package height	72 mm
Access Control List (ACL)	✓	Package weight	3 kg
IGMP snooping	✓	Logistics data	
Multicast features		Harmonized System (HS) code	85176990
Multicast support	✓	Other features	
Design		Dimensions (WxDxH)	440 x 210 x 44 mm
Rack mounting *	✓	Connectivity technology	Wired
Stackable *	✗	Packet transfer speed	23.8 Mpps
		Electromagnetic emissions	FCC Class A, CE Class A, IC Class A, VCCI Class A, C-Tick
		Performance management	Telnet, SNMP, SNMP
		Connectivity LEDs	✓

Design		Other features	
Product colour	Black	Input frequency	50/60 Hz
Safety	cUL, LVD		
Performance			
Mean time between failures (MTBF)	799491 h		
Technical details			
Shipping (inner) case height	38.6 cm		
Shipping (inner) case width	34.6 cm		



0790069332227



790069332227

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.