

## CyberPower BR1200ELCD uninterruptible power supply (UPS) Line-Interactive 1.2 kVA 720 W 8 AC outlet(s)

**Brand :** CyberPower

**Product code:** BR1200ELCD-UK

**Product name :** BR1200ELCD

- Line-interactive UPS Topology
  - Energy Saving Technology
  - Simulated Sine Wave Output
  - Automatic Voltage Regulation (AVR)
  - USB Charging Port
  - Surge and Spike Protection
  - Phone/ Fax/ Modem/ DSL/ Network Protection
  - LCD Status Display
  - PowerPanel® Management Software
  - Brick Form Factor
- Line-Interactive, 1200VA/720W, AVR, LCD



CyberPower BR1200ELCD uninterruptible power supply (UPS) Line-Interactive 1.2 kVA 720 W 8 AC outlet(s):

CyberPower BR1200ELCD offers home and office users a reliable battery backup and safeguards office PCs, network communication equipment, and other electronic devices from surges, spikes, brownouts and other power incidents. Designed with GreenPower UPS™ Technology to improve operating efficiency and to minimize energy consumption, users can enjoy significant energy cost savings over conventional UPS systems.



Features		Battery	
UPS topology *	Line-Interactive	Typical backup time at half load	9 min
Output power capacity *	1.2 kVA	Battery recharge time	8 h
Output power *	720 W	Charging current	1 A
Waveform *	Sine	Cold start	✓
Input operation voltage (min) *	170 V	<b>Design</b>	
Input operation voltage (max) *	290 V	Form factor *	Compact
Input frequency *	50/60 Hz	Housing material	Plastic
Output frequency	50/60 Hz	Cable length	1.5 m
Automatic Voltage Regulation (AVR)	✓	Product colour *	Black
Surge energy rating	125 J	Display type	LCD
Response time	4 ms	LED indicators	✓
EMI/RFI noise filtering	✓	Certification	CE , RCM
Noise level	40 dB	<b>Operational conditions</b>	
Surge protection	✓	Operating temperature (T-T)	0 - 40 °C
Surge protection features	Digital Subscriber Line (DSL), Fax, Modem, Network, Telephone	Storage temperature (T-T)	-20 - 50 °C
Power protection features	Overload	Operating relative humidity (H-H)	0 - 90%
Audible alarm(s)	✓	Storage relative humidity (H-H)	0 - 90%
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm	Operating altitude	0 - 3000 m
<b>Ports &amp; interfaces</b>		Non-operating altitude	0 - 3000 m
AC outlets quantity	8 AC outlet(s)	<b>Technical details</b>	
USB port	✓	Sustainability certificates	RoHS
USB 2.0 ports quantity	1	<b>Weight &amp; dimensions</b>	
Serial interface	✗	Width	166 mm
Modem (RJ-11) ports	2	Depth	288 mm
Ethernet LAN (RJ-45) ports	2	Height	118 mm
<b>Battery</b>		Weight	8.2 kg
Battery technology	Sealed Lead Acid (VRLA)		

<b>Battery</b>		<b>Packaging data</b>	
Typical backup time at full load	2 min	Bundled software	PowerPanel® Personal Edition
<b>Other features</b>			
Nominal output voltage			230 V
Nominal input voltage			230 V



4712856272741

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-MAR-2024. Prints or copies of Information are only valid on the printed Publication date